



## B2320/B2620/B2920 Compact Tractor Implements

Competitive Optional Implement Comparison						
LOADER MODEL		Kubota B2320 LA304 Loader	John Deere 2320 200CX Loader	Kubota B2620 / B2920 LA364 Loader	John Deere 2520 200CX Loader	New Holland T1110 210TL Loader
Lift Capacity (Pivot Pin)	lbs. (kg)	771 (350)	899 (408)	952 (432)	800 (363)	900 (408)
Lift Height (Pivot Pin)	in. (mm)	74 (1880)	78.7 (2000)	78.5 (1995)	78.7 (2000)	72.6 (1844)
Reach at Maximum Height	in. (mm)	23.5 (598)	28.3 (719)	22.7 (576)	29.2 (750)	27.8 (706)
Boom Breakout Force (Pivot Pin)	lbs. (kg)	1648 (748)	2262 (1026)	2144 (972)	2137 (969)	1492 (677)
Digging Depth at Bucket Level	in. (mm)	3.9 (100)	3.7 (93)	3.9 (100)	3.8 (97)	3.9 (100)
Cycle Times - Loader Raise	sec.	2.8	4.73	3.7	3.19	3.2
Cycle Times - Loader Lower	sec.	2.0	2.88	2.7	1.95	2.7
Cycle Times - Bucket Dump	sec.	1.5	4.73	1.9	3.19	2.0
Cycle Times - Bucket Rollback	sec.	1.9	2.88	2.6	1.95	1.5
Bucket Angle - Dump Angle	degrees	45	38	40	38	45
Bucket Angle - Rollback Angle	degrees	25	25	25	25	23
BACKHOE MODEL		Kubota B-20 Series BH65 Backhoe	John Deere 2320 46 Backhoe	Kubota B-20 Series BH65 Backhoe	John Deere 2520 46 Backhoe	New Holland T1110 Backhoe
Digging Depth at 2' flat bottom	in. (mm)	78.8 (2001)	78 (2000)	78.8 (2001)	78 (2000)	No Backhoe Available for New Holland T1110
Swing Arc	degrees	150	180	150	180	
Bucket Cylinder Digging Force	lbs. (kg)	2585 (1172)	2450 (1111)	2585 (1172)	2450 (1111)	
Dipperstick Cylinder Digging Force	lbs. (kg)	1686 (764)	1250 (567)	1686 (764)	1250 (567)	
Loading Height	in. (mm)	64.4 (1635)	60 (1500)	64.4 (1637)	60 (1500)	
Reach from Swing Point	in. (mm)	108.9 (2767)	101 (2600)	108.9 (2767)	101 (2600)	
Rotating Backhoe Operator Seat		Standard	N/A	Standard	N/A	
6-Positional Mechanical Thumb		Optional	N/A	Optional	N/A	

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge.

Kubota reserves the right to change the specifications relating to its products without notice.