



B2630 Compact Tractors

| Competitive Comparison | | | | | |
|------------------------|---|----------|-----------------|----------------------------|----------------------------|
| MODEL | | | Kubota B2630HSD | John Deere 2520 | |
| Engine | Engine gross power | | HP(kw) | 26.0 (19.4) | 26.5 (19.8) |
| | PTO power | | HP(kw) | 19.5 (14.5) | 20.5 (15.3) |
| | No. of cylinders | | | 3 | 3 |
| | Total displacement | | cu.in.(cm3) | 68.5 (1123) | 81.2 (1330) |
| | Fuel tank capacity | | gal.(l) | 8.1 (31) | 7.1 (27) |
| | Double air cleaner | | | Standard | Standard |
| Drive train | Transmission | | | HST (3-Ranges) | HST (2-Ranges) |
| | Max. traveling speed | | mph(km/h) | 13.4 (21.5) | N/P |
| | Brake | | | Wet, Disc | Wet, Disc |
| PTO | Independent PTO | | | Standard | Standard |
| | Mid PTO | | | Standard | Standard |
| Tires | Farm | Front | | 7-12 | N/P |
| | | Rear | | 12.4-16 | N/P |
| | Turf | Front | | 23X8.50-12 | 24x8.5-14 |
| | | Rear | | 13.6-16 | 36x14.00 |
| | R4 | Front | | 23X8.50-14 | 23x8.50-12 |
| | | Rear | | 12.4-16 | 36x14.00-17.5 |
| Hydraulic System | Pump capacity | | gpm(l/min) | 5.6+4.2 (21.2+16.0) | 5.5+5.0 (20.8+18.8) |
| | 3-Point Hitch lift capacity @ 24" behind lift point | | lbs.(kg) | 1676 (760) | 1150 (522) |
| | Position control | | | Standard | Standard |
| | Power steering | | | Hydrostatic Power Steering | Hydrostatic Power Steering |
| 3-Point Hitch | Telescopic lower link ends | | | Standard | N/P |
| | Lower link adjustment | | | Telescopic stabilizers | N/P |
| Generals | Cup Holder | | | Standard | N/P |
| | Toolbox | | | Standard | N/P |
| | Tilt steering wheel | | | Standard | N/P |
| | Deluxe seat with armrest | | | Standard | N/P |
| Dimensions | Wheelbase | | in.(mm) | 65.6 (1666) | 65.2 (1655) |
| | Tread | Front | in.(mm) | 36.8 (935) | 32.7 (830) |
| | | Rear | in.(mm) | 41.3 (1050) | N/P |
| | Min. ground clearance | | in.(mm) | 14.6 (370) | 12.5 (318.4) |
| | Overall Length w/3-Point Hitch | | in.(mm) | 110 (2796) | 108.9 (2766) |
| | Overall Height to top of ROPS | | in.(mm) | 78.6 (1997) | 90 (2279) |
| | Overall Width (min. tread) | | in.(mm) | 53.8 (1366) | N/P |
| Weight (w/ROPS) | | lbs.(kg) | 1829 (830) | 1865 (846) | |

N/A = Not Available

N/P = Not Published

These comparison of specifications are based upon the most reliable data obtained by Kubota at the time of publication.

Kubota reserves the right to change the specifications relating to its products without notice.

Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was being prepared. It is correct to the best of our knowledge.



B3030 Compact Tractors

| Competitive Comparison | | | | | | |
|------------------------|---|----------|-----------------|----------------------------|----------------------------|----------------------------|
| MODEL | | | Kubota B3030HSD | John Deere 2720 | New Holland T2210HSD | |
| Engine | Engine gross power | | HP(kw) | 30.0 (22.4) | 30.5 (22.7) | 31.0 (23.1) |
| | PTO power | | HP(kw) | 23.0 (17.1) | 23.5 (17.5) | 24.9 (18.6) |
| | No. of cylinders | | | 4 | 3 | 3 |
| | Total displacement | | cu.in.(cm3) | 91.4 (1498) | 100.2 (1641.9) | 91.3 (1496) |
| | Fuel tank capacity | | gal.(l) | 8.1 (31) | 7.1 (27) | 7.3 (27.6) |
| | Double air cleaner | | | Standard | Standard | Standard |
| Drive Train | Transmission | | | HST (3 ranges) | HST (2 Ranges) | HST (3 ranges) |
| | Max. traveling speed | | mph(km/h) | 13.4 (21.5) | 13.0 (20.9) | N/P |
| | Brake | | | Wet, Disc | Wet, Disc | Wet, Disc |
| PTO | Independent PTO | | | Standard | Standard | Standard |
| | Mid PTO | | | Standard | Standard | Standard |
| Tires | Farm | Front | | 7-12 | N/P | 7 x 14 |
| | | Rear | | 12.4-16 | N/P | 11.2 x 24 |
| | Turf | Front | | 23X8.50-12 | 24x8.5-14 | 27 x 10.5-15 |
| | | Rear | | 13.6-16 | 36x14.00-15 | 41 x 14-20 |
| | R4 | Front | | 23X8.50-14 | 23x8.5-12 R4 | 25 x 8.5-14 |
| | | Rear | | 12.4-16 | 14-17.5 R4 | 15 x 19.5 |
| Hydraulic System | Pump capacity | | gpm(l/min) | 5.2+3.9 (19.7+14.8) | 10.5 (20.8) | 7.2+5.1 (27.1+19.4) |
| | 3-Point Hitch lift capacity @ 24" behind lift point | | lbs.(kg) | 1676(760) | 1314 (596) | 1635 (743) |
| | Position control | | | Standard | Standard | Standard |
| | Power steering | | | Hydrostatic Power Steering | Hydrostatic Power Steering | Hydrostatic Power Steering |
| 3-Point Hitch | Telescopic lower link ends | | | Standard | N/P | N/P |
| | Lower link adjustment | | | Telescopic stabilizers | N/P | N/P |
| | Lift rod adjustment | | | Ratchet | N/P | N/P |
| Generals | Cup Holder | | | Standard | Standard | N/P |
| | Toolbox | | | Standard | Standard | Standard |
| | Cab | | | Optional | N/A | Standard |
| | Tilt steering wheel | | | Standard | N/P | Standard |
| | Deluxe seat with armrest | | | Standard | N/P | N/P |
| Dimensions | Wheelbase | | in.(mm) | 65.6 (1666) | 65.2 (1655) | 63.0 (1600) |
| | Tread | Front | in.(mm) | 36.8 (935) | 32.7 (830) | N/P |
| | | Rear | in.(mm) | 41.3 (1050) | 37.6 (954) | N/P |
| | Min. ground clearance | | in.(mm) | 14.6 (370) | N/P | N/P |
| | Overall Length w/3-Point Hitch | | in.(mm) | 99.2 (2520) | 108.9 (2766) | N/P |
| | Overall Height to top of ROPS | | in.(mm) | 78.6 (1997) | 90 (2279) | N/P |
| | Overall Width (min. tread) | | in.(mm) | 53.8 (1366) | 47.1 (1196) | N/P |
| Weight (w/ ROPS) | | lbs.(kg) | 1895 (860) | 1973 (895) | 2605 (1182) | |

N/A = Not Available

N/P = Not Published

These comparison of specifications are based upon the most reliable data obtained by Kubota at the time of publication.

Kubota reserves the right to change specifications without notice.

Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was being prepared.

It is correct to the best of our knowledge but due to technological developments it is subject to change without notice.