



B3200 Compact Tractor Implements

Competitive Optional Implement Comparison				
LOADER MODEL		Kubota B3200 LA504 Loader	John Deere 3032E 305 Loader	New Holland T1510 110TL Loader
Lift Capacity (Pivot Pin)	lbs. (kg)	1065 (483)	1186 (539)	875 (397)
Lift Height (Pivot Pin)	in. (mm)	82.6 (2098)	84 (2140)	100.5 (2553)
Reach at Maximum Height	in. (mm)	20.6 (524)	24 (603)	12.8 (324)
Boom Breakout Force (Pivot Pin)	lbs. (kg)	2474 (1122)	1704 (772)	1602 (727)
Digging Depth at Bucket Level	in. (mm)	2.3 (59)	5 (131)	4.0 (102)
Cycle Times - Loader Raise	sec.	2.8	3.31	N/A
Cycle Times - Loader Lower	sec.	2.5	2.75	N/A
Cycle Times - Bucket Dump	sec.	2	1.75	N/A
Cycle Times - Bucket Rollback	sec.	2.1	1.88	N/A
Bucket Angle - Dump Angle	degrees	37	43.8	38
Bucket Angle - Rollback Angle	degrees	23	31.4	20
Quick Attach Bucket		Yes	Yes	Pin On
Quick Attach Loader		Yes	Permanently Attached Loader	Yes
Factory Pallet Forks		Optional	Optional	N/A
BACKHOE MODEL		Kubota B3200 BH76 Backhoe	John Deere 3032E Backhoe	New Holland T1510 920GH Backhoe
Digging Depth at 2' flat bottom	in. (mm)	91.0 (2311)	No Backhoe Available for John Deere 3032E	89.9 (2283)
Swing Arc	degrees	180		180
Bucket Cylinder Digging Force	lbs. (kg)	3339 (1514)		2875 (1304)
Dipperstick Cylinder Digging Force	lbs. (kg)	2097 (951)		2020 (916)
Loading Height	in. (mm)	64.4 (1636)		69.8 (1773)
Reach from Swing Point	in. (mm)	120.5 (3060)		123 (3124)
Rotating Backhoe Operator Seat		Standard		N/A
6-Positional Mechanical Thumb		Optional	N/A	

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.