



B3300SU Compact Tractors

Competitive Comparison						
MODEL			Kubota B3300SU	John Deere 3032E	New Holland T1510	
Engine	Engine gross power	HP(kw)	33 (24.6)	31.4 (23.4)	30 (22.4)	
	PTO power	HP(kw)	25 (18.6)	25 (18.6)	24.0 (17.9)	
	No. of cylinders		4	3	3	
	Total displacement	cu.in.(cm3)	91.5 (1498)	97.6 (1599)	91.3 (1496)	
	Fuel tank capacity	gal.(l)	8.1 (31)	6.4 (24.2)	7.1 (27)	
Drive Train	Transmission		HST (3 range)	HST (2 range)	HST (3 range)	
	Max. traveling speed	mph(km/h)	12.8 (20.6)	12.4 (20)	13.6 (21.9)	
	Brake		Wet, Disc	Wet, Disc	Wet, Disc	
PTO	Rear PTO Type		Live Continuous	Independent	Live Continuous	
	Mid PTO Type		N/P	N/P	Live Continuous	
Tires	Farm	Front	7-12	7-14	7.4 x 14	
		Rear	12.4-16	11.2-24	11.2 x 24	
	Turf	Front	24x8.50-14	27x8.5-15	24 x 8.50-14	
		Rear	13.6-16	41x14.0-20	13.6 x 16	
	R4	Front	25x8.5-14	25x8.5-14	25 x 8.50-14	
		Rear	15-19.5	15.00-19.5	15 x 19.5	
Hydraulic System	Total Pump capacity	gpm(l/min)	9.9 (37.5)	9.3 (35.2)	10 (37.9)	
	3-Point Hitch lift capacity @ 24" behind lift point	lbs.(kg)	1300 (590)	1356 (615)	1635 (743)	
	3 Point Hitch Valve Type		Quarter Inching Valve	Position Control	N/P	
	Power steering		Integral Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	
	Integrated Loader Control Valve		Standard	N/P	N/P	
Generals	Cup Holder		Standard	Standard	Standard	
	Toolbox		Standard	N/P	N/P	
Dimensions	Wheelbase	in.(mm)	66.8 (1696)	60 (1525)	63.0 (1600)	
	Tread	Front	in.(mm)	36.2 (920)	41.7 (1058) - 50.3 (1278)	43.4 (1102)
		Rear	in.(mm)	42.7 (1085)	N/P	42.8 (1087)
	Min. ground clearance	in.(mm)	15.6 (395)	13.0 (330)	12.2 (310)	
	Overall length w/3-Point Hitch	in.(mm)	109.8 (2789)	111 (2819)	111.4 (2830)	
	Overall height	in.(mm)	89.8 (2280)	82.3 (2090)	82.3 (2090)	
	Overall width	in.(mm)	57.9 (1470)	56.5 (1435)	46.1 (1170)	
Weight (w/ROPS)	lbs.(kg)	1929 (875)	2175 (987)	2385 (1082)		

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.