



F2680/F3080/F3680 Front Mowers

Competitive Comparison							
MODEL		Kubota F2680/F3080/F3680	John Deere 1445(2, 4WD)/1565 4WD	Toro 328D 2WD/4WD	Jacobsen 628D 2WD / 4WD	New Holland MC28 2WD/MC35 4WD	
Engine	Type	Kubota Diesel	Yanmar Diesel	Kubota Diesel	Kubota Diesel	Shibaura Diesel	
	Engine Horsepower (HP)	25.5 / 30 / 36	31/36	28	26	28/35	
	Number of Cylinders	3 / 3 / 4	3	3	4	3	
Drive Train	Transmission	HST (F2/R2)	HST FR1(2WD)/ F2 R2	HST FR1/ F2 R2	HST FR1/ F2 R2	HST FR1/ F2 R2	
	Travel Speed (mph)	Forward	12.5	15-Dec	9.5	8.25 / 10	10.7
		Reverse	6.8	5	9.5	3/4	7
	Differential Lock	Yes	Yes	Yes	Yes	Yes	
	2WD/4WD	2WD/4WD/4WD	2WD, 4WD	2WD, 4WD	2WD, 4WD	2WD, 4WD	
	Auto Assist 4WD	Forward/Reverse	Forward	Forward	-	-	
	Drive Mower	Shaft	Shaft	Shaft	Hydraulic	Shaft	
Mower Clutch	Hydraulic Clutch	Hydraulic Clutch	Electric Clutch	Hydraulic Clutch	Hydraulic Clutch		
Maintenance	Fuel Tank Capacity (gal.)	16.1	16	11.3	-	13.3	
	Air Cleaner	Indicator	Yes: F3680	Yes	-	-	Yes
		Dual Element	Yes	Yes	Yes	-	Yes
	Fuel Gauge	Electric Meter	Mechanical Meter	Meter	Meter	Mechanical Meter	
	Tachometer	OPT	No	No	No	-	
Tool Box	Yes	No	Yes	Yes	-		
Comfort	Seat with Adjustable Controls	Armrest Adj.	Yes	No	Opt	No	-
		Lumbar Adj.	Yes	No	No	No	-
		Back Angle Adj.	Yes	No	No	No	-
		Wgt. Ctrl. Adj.	Yes	No	No	No	-
Mower Deck	Discharge Type/Size	Side Discharge	60" / 72"	60" / 72"	60" / 72"	63" / 72"	60" / 72"
		Rear Discharge	60" / 72"	62" / 72"	60" / 72"	60" / 72"	60" / 72"
	Front Baffle Kit (Fine Cut)	Opt (Side Discharge)	No	No	No	n	
	Mulching Kit	Side Discharge	Opt	Opt	Opt	Mulching Deck	Opt
		Rear Discharge	Opt	No	Opt	Mulching Deck	Opt
	Deck-Pan	Side Discharge	Welded	Stamped	Welded/Stamp	Welded	Welded
		Rear Discharge	Welded	Welded	Welded/Stamp	Welded	Welded
	Cutting Height (Min-Max) (inch)	1.0- 5.0	1.0 - 6.0	1.0 - 5.0	1.0 - 4.75	1.5 - 4.5	
	Cutting Height Increments (inch)	0.25	0.5	0.5	0.25	-	
	Tilt Assist	Yes: 72" Decks	No	No	No	No	
	Tilt Angle	60" Side	90°	90°	-	-	90°
		72" Side	90°	90°	-	-	90°
60"/62" Rear		90°	70°	-	-	90°	
72" Rear		90°	90°	-	-	90°	

- : Information not available. This comparison of specifications is based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice. Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was prepared. It is correct to the best of our knowledge, but due to technological developments, it is subject to change without notice.