



## L2800 Compact Tractor Implements

Competitive Optional Implement Comparison						
LOADER MODEL		Kubota L2800 LA463 Loader	John Deere 3005 300 Loader	John Deere 3032E 305 Loader	New Holland 1510 110TL Loader	
Lift Capacity (Pivot Pin)	lbs. (kg)	1142 (518)	741 (336)	1186 (537)	875 (397)	
Lift Height (Pivot Pin)	in. (mm)	95.3 (2420)	86.6 (2199)	84 (2133)	100.5 (2553)	
Reach at Maximum Height	in. (mm)	22.2 (565)	33 (838)	24 (609)	12.8 (324)	
Boom Breakout Force (Pivot Pin)	lbs. (kg)	2442 (1107)	1729 (784)	1704 (772)	1602 (727)	
Digging Depth at Bucket Level	in. (mm)	5.9 (150)	3.5 (88.9)	5 (131)	4.0 (102)	
Cycle Times - Loader Raise	sec.	3.5	3.2	3.31	N/P	
Cycle Times - Loader Lower	sec.	2.2	1.63	2.75	N/P	
Cycle Times - Bucket Dump	sec.	1.7	2.71	1.75	N/P	
Cycle Times - Bucket Rollback	sec.	2.1	1.38	1.88	N/P	
Bucket Angle - Dump Angle	degrees	40	40.5	43.8	38	
Bucket Angle - Rollback Angle	degrees	31	24.3	31.4	20	
Quick Attach Bucket		YES	Optional	YES	N/A	
Quick Attach Loader		YES	YES	Permanently Attached Loader	N/A	
Factory Pallet Forks		Optional	Optional	Optional	N/A	
BACKHOE MODEL		Kubota L2800 BH76 Backhoe	John Deere 3005 7 Backhoe	John Deere 3032E Backhoe	New Holland 1510 920GH Backhoe	
Digging Depth at 2' flat bottom	in. (mm)	91.0 (2311)	90.0 (2286)	No Backhoe Available for John Deere 3032E	89.9 (2283)	
Swing Arc	degrees	180	180		180	
Bucket Cylinder Digging Force	lbs. (kg)	3339 (1514)	1945 (882)		2875 (1304)	
Dipperstick Cylinder Digging Force	lbs. (kg)	2097 (951)	1095 (496)		2020 (916)	
Loading Height	in. (mm)	64.4 (1636)	69.0 (1752)		69.8 (1773)	
Reach from Swing Point	in. (mm)	120.5 (3060)	114 (2895)		123 (3124)	
6-Positional Mechanical Thumb		Optional	N/A		NO	

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge.



## L3400 Compact Tractor Implements

Competitive Optional Implement Comparison				
LOADER MODEL		Kubota L3400 LA463 Loader	John Deere 3038E 305 Loader	New Holland 1520 110TL Loader
Lift Capacity (Pivot Pin)	lbs. (kg)	1142 (518)	1186 (537)	875 (397)
Lift Height (Pivot Pin)	in. (mm)	95.3 (2420)	84 (2133)	100.5 (2553)
Reach at Maximum Height	in. (mm)	22.2 (565)	24 (609)	12.8 (324)
Boom Breakout Force (Pivot Pin)	lbs. (kg)	2442 (1107)	1704 (772)	1602 (727)
Digging Depth at Bucket Level	in. (mm)	5.9 (150)	5 (127)	4.0 (102)
Cycle Times - Loader Raise	sec.	3.5	3.31	N/P
Cycle Times - Loader Lower	sec.	2.2	2.75	N/P
Cycle Times - Bucket Dump	sec.	1.7	1.75	N/P
Cycle Times - Bucket Rollback	sec.	2.1	1.88	N/P
Bucket Angle - Dump Angle	degrees	40	43.8	38
Bucket Angle - Rollback Angle	degrees	31	31.4	20
Quick Attach Bucket		YES	YES	N/A
Quick Attach Loader		YES	N/A	N/A
Factory Pallet Forks		Optional	Optional	N/A
BACKHOE MODEL		Kubota L3400 BH76 Backhoe	John Deere 3038E Backhoe	New Holland 1520 920GH Backhoe
Digging Depth at 2' flat bottom	in. (mm)	91.0 (2311)	No Backhoe Available for John Deere 3038E	89.9 (2283)
Swing Arc	degrees	180		180
Bucket Cylinder Digging Force	lbs. (kg)	3339 (1514)		2875 (1304)
Dipperstick Cylinder Digging Force	lbs. (kg)	2097 (951)		2020 (916)
Loading Height	in. (mm)	64.4 (1636)		69.8 (1773)
Reach from Swing Point	in. (mm)	120.5 (3060)		123 (3124)
6-Positional Mechanical Thumb		Optional		NO

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.



## L4400 Compact Tractor Implements

Competitive Optional Implement Comparison					
LOADER MODEL		Kubota L4400DT/HST LA703A Loader	John Deere 4005 300CX Loader	John Deere 4105 300CX Loader	New Holland T1530 250TL Loader
Lift Capacity (Pivot Pin)	lbs. (kg)	1818 (825)	1256 (571)	1393 (633)	2000 (907)
Lift Height (Pivot Pin)	in. (mm)	102.4 (2600)	103.9 (2640)	103.3 (2616)	105 (2667)
Reach at Maximum Height	in. (mm)	19 (483)	21.7 (551)	30.1 (766)	33 (838)
Boom Breakout Force (Pivot Pin)	lbs. (kg)	3378 (1532)	3015 (1368)	3769 (1710)	3540 (1606)
Digging Depth at Bucket Level	in. (mm)	3.5 (90)	4 (104)	4.76 (121)	6.5
Cycle Times - Loader Raise	sec.	3.3	3.57	3.6	4.2
Cycle Times - Loader Lower	sec.	2.2	2.1	2.1	3.2
Cycle Times - Bucket Dump	sec.	1.3	3.04/1.24(with regen)	3.0 / 1.2 (with regen)	1.9
Cycle Times - Bucket Rollback	sec.	2.2	1.79	1.8	2.6
Bucket Angle - Dump Angle	degrees	40	45	49.3	58
Bucket Angle - Rollback Angle	degrees	23	27	23.8	30
Quick Attach Bucket		YES	Optional	Optional	Optional
Quick Attach Loader		YES	YES	YES	Yes
Factory Pallet Forks		Optional	Optional	Optional	Optional
BACKHOE MODEL		Kubota L4400DT/HST BH92 Backhoe	Deere 4005 8B Backhoe	Deere 4105 375 Backhoe	New Holland T1530 Backhoe
Digging Depth at 2' flat bottom	in. (mm)	109.8	102 (2590)	105 (2667)	No Backhoe Available for the New Holland T1530
Swing Arc	degrees	180	180	180	
Bucket Cylinder Digging Force	lbs. (kg)	4548	3389 (1537)	2840 (1288)	
Dipperstick Cylinder Digging Force	lbs. (kg)	2698	2213 (1003)	2005 (909)	
Loading Height	in. (mm)	83.4	82 (2082)	78.5 (1993)	
Reach from Swing Point	in. (mm)	150.4	133 (3378)	124 (3149)	

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without prior notice.