



L2800 Compact Tractors

Competitive Comparison								
MODEL		Kubota L2800-1		John Deere 3005	John Deere 3032E	New Holland T1510		
		Gear 2WD/4WD	HST 4WD	Gear	HST 4WD	Gear 2WD/4WD	HST 4WD	
Engine	Engine gross power	HP(kw)	30.0 (22.4)		27 (17.9)	31.4 (23.4)	30.0 (22.4)	
	PTO power	HP(kw)	25.0 (18.6)	23.5 (17.5)	24 (17.6)	25 (18.6)	25.5 (19.0)	24.0 (17.9)
	No. of cylinders		3		3	3	3	
	Total displacement	cu.in.(cm3)	91.5 (1499)		81.2 (1331)	97.6 (1599)	91.3 (1496.1)	
	Rated revolution		2800		2700	2500	2600	
	Fuel tank capacity	gal.(l)	9.0 (34.0)		6.3 (23.8)	6.4 (24.2)	7.1 (27)	
	Air cleaner		Single Element (Dual Optional)		Dry Type Air Cleaner w/ Safety Element	Dry Type Air Cleaner w/ Safety Element	Dual Element	
Drive train	Transmission		Sliding Gear & Constant Mesh	HST	Gear	HST 4WD	Gear	HST
	No. of traveling speeds		8F/4R	3-Range	8F/2R	2-Range	9F/3R	3-Range
	Max. traveling speed	mph(km/h)	13.7 (22.0)	14.7 (23.6)	12.7 (20.5)	12.4 (20)	12.1 (19.5)	13.6 (21.9)
	Brake		Multiple Wet, Disc		Dry Shoe	Wet, Disc	Wet, Disc	
	PTO clutch		Transmission driven w/ overrunning clutch	Continuous Live	Continuous Live	Independent	Transmission Driven/ Live (Optional)	Continuous Live
Tires	Farm	Front	5-15/11.2 - 24		2WD: 5.9 - 15 4WD: 7 - 14	7 - 14	7.4 x 14	
		Rear	7-16/11.2 - 24		2wd: 11.2 - 24 4wd: 11.2 - 24	11.2-24	11.2 x 24	
	Turf	Front	23 x 8.50 - 12		25 x 8.50 - 14 4PR	27 x 8.5 - 15	24 x 8.50 - 14	
		Rear	13.6 - 16		13.6 - 16 4PR	41 x 14.0 - 20	13.6 x 16	
	R4	Front	N/A	27 x 8.50 - 15	25 x 8.50 - 14 6PR	25 x 8.5 - 14	25 x 8.50 - 14	
		Rear	N/A	15 - 19.5	15.0 - 19.5 6PR	15.00 - 19.5	15 x 19.5	
Hydraulic System	Pump capacity	gpm(l/min)	10.5 (39.7)		9.4 (36.5)	9.3 (35.2)	6.2 (23.3)	
	3-Point Hitch lift capacity @ 24" behind lift point	lbs.(kg)	1435 (651)		815 (370)	1356 (615)	1635 lb. (743)	
	Power steering		Integral Type Power Steering		Standard	Hydrostatic Power Steering	Standard (Hydrostatic)	
Dimensions	Wheelbase	in.(mm)	63.3 (1610)		61 (1550)	60 (1525)	63.0 (1600)	
	Overall Length (w/ 3pt.)	in.(mm)	119.1 (3025)	115.0 (2920)	111 (2821)	111 (2819)	111.4 (2830)	
	Overall Height (w/ ROPS)	in.(mm)	85.0 (2160)		82 (2083)	82.3 (2090)	82.3 (2090)	
	Overall width (min. tread)	in.(mm)	51.4 (1305)		54 (1362)	56.5 (1435)	46.1 (1170)	
	Min. ground clearance	in.(mm)	13.6 (345)	13.4 (340)	N/P	13.0 (330)	12.2 (310)	
	Min. turning radius w/ brake	ft.(m)	7.9 (2.4) / 8.2 (2.5)	8.2(2.5)	7 (2.1)	N/P	8.0 (2.5)	
	Weight (w/ROPS)	lbs.(kg)	2359 (1070) / 2536 (1150)	2600 (1180)	2WD: 1929 (875) 4WD: 2105 (955)	2175 (987)	2385 (1082)	

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.



L3400 Compact Tractors

Competitive Comparison							
MODEL		Kubota L3400-1		John Deere 3038E	New Holland T1520		
		Gear 2WD/4WD	HST 4WD	HST 4WD	Gear 4WD	HST 4WD	
Engine	Engine gross power	HP(kw)	35.7 (26.6)		37.1 (27.3)	35.0 (26.1)	
	PTO power	HP(kw)	30.0 (22.4)	28.5 (21.3)	30.0 (22.4)	29.5 (21.9)	28 (20.9)
	No. of cylinders		3		3	3	
	Total displacement	cu.in.(cm3)	111.4 (1826)		91.5 (1499)	101.4 (1662)	
	Rated revolution		2700		2500	2600	
	Fuel tank capacity	gal.(l)	9.0 (34.0)		6.4 (24.2)	7.1 (26.9)	
	Air cleaner		Single Element (Dual Optional)		Dry Type Air Cleaner with Safety Element	Dual Element	
Drive train	Transmission		Sliding Gear & Constant Mesh	HST	HST	Gear	HST 4WD
	No. of traveling speeds		8F/4R	3-Range	2-Range	9F/3R	3-Range
	Max. traveling speed	mph(km/h)	13.2 (21.2)	14.1 (22.7)	12.4 (20.0)	12.1 (19.5)	13.6 (21.9)
	Brake		Multiple Wet, Disc		Wet, Disc	Wet, Disc	
	PTO clutch		Continuous Live	Continuous Live	Independent	Continuous Live	Continuous Live
Tires	Farm	Front	2WD: 5.00 - 15 4WD: 7.00 - 16	7.00 - 16	7 - 14	7 x 14	
		Rear	2WD: 11.2 - 24 4WD: 11.2 - 24	11.2 - 24	11.2 - 24	11.2 x 24	
	Turf	Front	2WD: 23 x 8.50 - 12 4WD: 24 x 8.50 - 14	24 x 8.50 - 14	27 x 8.5 - 15	24 x 8.50 - 14	
		Rear	2WD: 13.6 - 16 4WD: 13.6 - 16	13.6 - 16	41 x 14 - 20	13.6 x 16	
	R4	Front	2WD: N/A 4WD: 27 x 8.50 - 15	27 x 8.50 - 15	25 x 8.5 - 14	25 x 8.50 - 14	
		Rear	2WD: N/A 4WD: 15 - 19.5	15 - 19.5	15 - 19.5	15 x 19.5	
Hydraulic System	Pump capacity	gpm(l/min)	10.1 (38.2)		9.3 (35.2)	6.2 (23.2)	
	3-Point Hitch lift capacity @ 24" behind lift point	lbs.(kg)	1435 (651)		1356 (615)	1635 (743)	
	Power steering		Integral Power Steering		Hydrostaic Power Steering	Hydrostaic Power Steering	
Dimensions	Wheelbase	in.(mm)	63.3 (1610)		60 (1525)	63.0 (1600)	
	Overall Length (w/ 3pt.)	in.(mm)	119.1 (3025)	115.0 (2920)	111 (2819)	111.4 (2830)	
	Overall Height (w/ ROPS)	in.(mm)	85.0 (2160)		82.3 (2090)	82.3 (2090)	
	Overall width (min. tread)	in.(mm)	51.4 (1305)		56.5 (1435)	46.1 (1170)	
	Min. ground clearance	in.(mm)	13.6 (345)	13.4 (340)	13 (330)	12.2 (310)	
	Min. turning radius w/ brake	ft.(m)	7.9 (2.4) / 8.2 (2.5)	8.2(2.5)	N/A	8.2 (2.5)	
	Weight (w/ROPS)	lbs.(kg)	2403 (1090)/2580 (1170)	2600 (1180)	2087 (947)	2385 (1082)	

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.

Kubota

L4400 Compact Tractors

Competitive Comparison

MODEL		Kubota L4400DT-1	New Holland T1530	John Deere 4005	Kubota L4400HST-1	New Holland T1530	John Deere 4105		
Engine	Engine gross power	HP(kw)	45.3 (33.8)	45.0 (33.6)	41.0 (30.5)	45.3 (33.8)	45.0 (33.6)	40.5 (30.1)	
	PTO power	HP(kw)	37.5(28.0)	38 (28.3)	35 (26.1)	36.0 (26.8)	36 (26.8)	32.5 (24.2)	
	No. of cylinders		4	4	4	4	4	3	
	Total displacement	cu.in.(cm3)	134.1 (2197)	135.2 (2215)	121.7 (1994)	134.1 (2197)	135.2 (2215)	91.5 (1.5)	
	Rated revolution		2600	2600	2700	2600	2600	2800	
	Fuel tank capacity	gal.(l)	11.1 (42.0)	10.3 (38.9)	8.5 (32)	11.1 (42.0)	10.3 (38.9)	10.5 (39.7)	
Drive train	Transmission		Gear	Gear	Gear	HST	HST	HST	
	No. of traveling speeds		8F/4R	12x12	9F/3R	3-Range	3-Range	2-Range	
	Max. traveling speed	mph(km/h)	14.9 (24.0)	13.6 (21.9)	11.9 (19.1)	15.8 (25.4)	13.6 (21.9)	N/P	
	Brake		Wet, Disc	Wet, Disc	Wet Disk	Wet, Disc	Wet, Disc	Wet, Disc	
	PTO clutch		Live-independent hydraulic PTO w/ PTO brake, wet clutch	Live	Independent	Live-independent hydraulic PTO w/ PTO brake, wet clutch	Independent	Independent	
Tires	Farm	Front	8.3-16	8x16	2wd: 6.5-16 4wd: 8-16	8.3-16	8x16	8-16	
		Rear	14.9-24	14.9x24	2wd: 14.9-24 4wd: 14.9-24	14.9-24	14.9x24	14.9-24	
	Turf	Front	27-10.5/44x18-20	27x10.5-15	N/P	27-10.5/44x18-20	27x10.5-15	N/A	
		Rear	27x8.50-15/44x18-20	44x18-20	N/P	27x8.50-15/44x18-20	44x18-20	N/A	
	R4	Front	10.0-16.5	10x16.5	N/P	10.0-16.5	10x16.5	10.00-16.5	
		Rear	17.5-24	17.5x24	N/P	17.5-24	17.5x24	17.5L-24	
Hydraulic System	Pump capacity	gpm(l/min)	7.8 (29.4)	9.8 (37.1)	8.5 (32.2)	7.8 (29.4)	9.8 (37.1)	14.8 (56.2)	
	3-Point Hitch lift capacity @ 24" behind lift point	lbs.(kg)	2310 (1053)	2330 (1056)	2020 (916.3)	2310 (1053)	2330 (1056)	2200 (999)	
	Power steering		Standard (Hydrostatic)	Standard (Hydraulic)	Standard	Standard (Hydrostatic)	Standard (Hydraulic)	N/P	
Dimensions	Wheelbase	in.(mm)	72.6 (1844)	73.5 (1867)	69 (1750)	72.6 (1844)	73.5 (1867)	68 (1727)	
	Overall Length (w/ 3pt.)	in.(mm)	125.6 (3190)	122 (3098)	124 (3142)	118.3 (3005)	122 (3098)	N/P	
	Overall Height (w/ ROPS)	in.(mm)	85.4 (2170)	97.4 (2473)	85 (2149)	85.4 (2170)	97.4 (2473)	N/P	
	Tread	Front	in.(mm)	45.5 (1155)	N/P	2wd: 48.2 (1224) 4wd: 54 (1372)	45.5 (1155)	N/P	N/P
			in.(mm)	46.5 (1180) 47.2 (1200) 51.2 (1300) 57.1 (1450) 60.8 (1545)	N/P	46 (1168)	46.5 (1180) 47.2 (1200) 51.2 (1300) 57.1 (1450) 60.8 (1545)	N/P	N/P
		Rear	in.(mm)						
			in.(mm)						
in.(mm)									
Min. ground clearance	in.(mm)	15.2 (385)	N/P	N/P	15.2 (385)	N/P	N/P		
Weight (w/ROPS)	lbs.(kg)	3153 (1430)	3311 (1502)	2WD: 2954 (1340) 4WD: 3174 (1440)	3307 (1500)	3311 (1502)	2987 (1355)		

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without prior notice.