



L3200 Compact Tractor Implements

Competitive Optional Implement Comparison					
LOADER MODEL		Kubota L3200 LA524 Loader	John Deere 3005 300 Loader	John Deere 3032E 305 Loader	New Holland 1510 110TL Loader
Lift Capacity (Pivot Pin)	lbs.	1131	741	1186	875
Lift Height (Pivot Pin)	in.	94.3	86.6	84	100.5
Reach at Maximum Height	in.	22.2	33	24	12.8
Boom Breakout Force (Pivot Pin)	lbs.	2462	1729	1704	1602
Digging Depth at Bucket Level	in.	6.9	3.5	5	4.0
Cycle Times - Loader Raise	sec.	3.4	3.2	3.31	N/P
Cycle Times - Loader Lower	sec.	2.2	1.63	2.75	N/P
Cycle Times - Bucket Dump	sec.	N/P	2.71	1.75	N/P
Cycle Times - Bucket Rollback	sec.	N/P	1.38	1.88	N/P
Bucket Angle - Dump Angle	degrees	42	40.5	43.8	38
Bucket Angle - Rollback Angle	degrees	31	24.3	31.4	20
Quick Attach Bucket		Optional	Optional	YES	N/A
Quick Attach Loader		YES	YES	Permanently Attached Loader	N/A
Factory Pallet Forks		Optional	Optional	Optional	N/A
BACKHOE MODEL		Kubota L3200 BH77 Backhoe	John Deere 3005 7 Backhoe	John Deere 3032E Backhoe	New Holland 1510 920GH Backhoe
Digging Depth at 2' flat bottom	in.	92.5	90.0	No Backhoe Available for John Deere 3032E	89.9
Swing Arc	degrees	180	180		180
Bucket Cylinder Digging Force	lbs.	3421	1945		2875
Dipperstick Cylinder Digging Force	lbs.	2190	1095		2020
Loading Height	in.	67.2	69.0		69.8
Reach from Swing Point	in.	124.2	114		123
6-Positional Mechanical Thumb		Optional	N/A		NO

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.



L3800 Compact Tractor Implements

Competitive Optional Implement Comparison

LOADER MODEL		Kubota L3800 LA524 Loader	John Deere 3038E 305 Loader	New Holland 1520 110TL Loader
Lift Capacity (Pivot Pin)	lbs.	1131	1186	875
Lift Height (Pivot Pin)	in.	94.3	84	100.5
Reach at Maximum Height	in.	22.2	24	12.8
Boom Breakout Force (Pivot Pin)	lbs.	2462	1704	1602
Digging Depth at Bucket Level	in.	6.9	5	4.0
Cycle Times - Loader Raise	sec.	3.4	3.31	N/P
Cycle Times - Loader Lower	sec.	2.2	2.75	N/P
Cycle Times - Bucket Dump	sec.	N/P	1.75	N/P
Cycle Times - Bucket Rollback	sec.	N/P	1.88	N/P
Bucket Angle - Dump Angle	degrees	42	43.8	38
Bucket Angle - Rollback Angle	degrees	31	31.4	20
Quick Attach Bucket		Optional	YES	N/A
Quick Attach Loader		YES	Permanently Attached Loader	N/A
Factory Pallet Forks		Optional	Optional	N/A
BACKHOE MODEL		Kubota L3800 BH77 Backhoe	John Deere 3038E Backhoe	New Holland 1520 920GH Backhoe
Digging Depth at 2' flat bottom	in.	92.5	No Backhoe Available for John Deere 3038E	89.9
Swing Arc	degrees	180		180
Bucket Cylinder Digging Force	lbs.	3421		2875
Dipperstick Cylinder Digging Force	lbs.	2190		2020
Loading Height	in.	67.2		69.8
Reach from Swing Point	in.	124.2		123
6-Positional Mechanical Thumb		Optional		NO

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.