



Kubota®

L3200 Compact Tractors

Competitive Comparison									
MODEL		Kubota L3200		John Deere 3005	John Deere 3032E	New Holland T1510			
		Gear 2WD/4WD	HST 4WD	Gear	HST 4WD	Gear 2WD/4WD	HST 4WD		
Engine	Engine gross horsepower	HP	31.9		27.5	31.4		30.0	
	Net horsepower	HP	30.4		N/A	N/A		N/A	
	PTO horsepower	HP	F/DT:26.7	HST: 25.2	23.5	25		25.5 24.0	
	No. of cylinders		3		3	3		3	
	Total displacement	cu.in.	91.5		81.2	97.6		91.3	
	Rated revolution		2800		2700	2500		2600	
	Fuel tank capacity	gal.	10		6.3	6.4		7.1	
	Air cleaner		Single Element (Dual Optional)		Dry Type Air Cleaner with Safety Element	Dry Type Air Cleaner with Safety Element		Dual Element	
Drive train	Transmission		Gear 2WD/4WD	HST	Gear	HST		Gear HST	
	No. of traveling speeds		F/DT: 8F/4R	3-Range	8F/2R	2-Range		9F/3R 3-Range	
	Max. traveling speed	mph	DT: 13.2	HST: 14.1	12.7	12.4		12.1 13.6	
	Brake		Multiple Wet, Disc		Dry Shoe	Wet, Disc		Wet, Disc	
	PTO clutch		Transmission driven w/ overrunning clutch	Continuous Live	Continuous Live	Independent		Transmission Driven / Live Continuous Live	
Tires	Farm	Front	2WD: 5.00-15 / 4WD 7.2-16		2WD: 5.0-15 / 4WD: 7 - 14		7 - 14		7.4 x 14
		Rear	11.2-24		2WD: 11.2 - 24 / 4WD: 11.2		11.2-24		11.2 x 24
	Turf	Front	25 x 8.50-14		25 x 8.50 - 14		27 x 8.5 - 15		24 x 8.50 - 14
		Rear	13.6-16		13.6 - 16		41 x 14.0 - 20		13.6 x 16
	R4	Front	4WD: 27 x 8.50-15		25 x 8.50 - 14		25 x 8.5 - 14		25 x 8.50 - 14
		Rear	4WD: 15-19.5		15.0 - 19.5		15.00 - 19.5		15 x 19.5
Hydraulic System	Pump capacity	gpm	10.5		9.4	9.3		6.2	
	3-Point Hitch lift capacity @ 24" behind lift point	lbs.	1,435		815	1356		1635	
	Power steering		Integral Power Steering		Standard	Hydrostatic Power Steering		Hydrostatic	
Dimensions	Wheelbase	in.	63.3		61	60		63.0	
	Overall Length (w/ 3pt.)	in.	2WD: 118.1 / 4WD: 114.8		111	111		111.4	
	Overall Height (w/ ROPS)	in.	91.7		82	82.3		82.3	
	Overall width (min. tread)	in.	55.1		54	56.5		46.1	
	Min. ground clearance	in.	2WD: 13.6 / 4WD: 13.4		N/P	13.0		12.2	
	Min. turning radius w/ brake	ft.	2WD: 7.9	4WD: 8.2	7	N/P		8.0.	
	Weight (w/ROPS)	lbs.	2WD F: 2,245 / 4WD DT: 2,601 / 4WD HST: 2,623		2WD: 1929 / 4WD: 2105		2175		2385

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the

Kubota®

L3800 Compact Tractors

Competitive Comparison									
MODEL		Kubota L3800		Kubota L3400-1	John Deere 3038E	New Holland T1520			
		Gear 2WD/4WD	HST 4WD	HST 4WD	HST 4WD	Gear 4WD	HST 4WD		
Engine	Engine gross horsepower	HP	37.4		35.7	37.1		35.0	
	Net horsepower	HP	35.9		34.2	N/A		N/A	
	PTO horsepower	HP	DT/F: 31.5	HST: 30.0	28.5	30.0		29.5	28
	No. of cylinders		3		3	3		3	
	Total displacement	cu.in.	111.4		111.4	91.5		101.4	
	Rated revolution		2700		2700	2500		2600	
	Fuel tank capacity	gal.	10		9.0	6.4		7.1	
	Air cleaner		Single Element (Dual Optional)		Single Element (Dual Optional)	Dry Type Air Cleaner with Safety Element		Dual Element	
Drive train	Transmission		Sliding Gear & Constant Mesh	HST	HST	HST		Gear	HST 4WD
	No. of traveling speeds		8F/4R	3-Range	3-Range	2-Range		9F/3R	3-Range
	Max. traveling speed	mph			14.1	12.4		12.1	13.6
	Brake		Multiple Wet, Disc		Multiple Wet, Disc	Wet, Disc		Wet, Disc	
	PTO clutch		Live PTO with overrunning		Continuous Live	Independent		Continuous Live	Continuous Live
Tires	Farm	Front	2WD: 5.00 - 15 / 4WD: 7 - 16		7.00 - 16	7 - 14		7 x 14	
		Rear	2WD/4WD: 11.2-24		11.2 - 24	11.2 - 24		11.2 x 24	
	Turf	Front	25 x 8.50 - 14		25 x 8.50 - 14	27 x 8.5 - 15		24 x 8.50 - 14	
		Rear	13.6 - 16		13.6 - 16	41 x 14 - 20		13.6 x 16	
	R4	Front	4WD: 27 x 8.50-15		27 x 8.50 - 15	25 x 8.5 - 14		25 x 8.50 -14	
		Rear	4WD: 15 - 19.5		15 - 19.5	15 - 19.5		15 x 19.5	
Hydraulic System	Pump capacity	gpm	10.1		10.1	9.3		6.2	
	3-Point Hitch lift capacity @ 24" behind lift point	lbs.	1,435		1,435	1356		1635	
	Power steering		Integral Power Steering		Integral Power	Hydrostaic Power Steering		Hydrostaic Power Steering	
Dimensions	Wheelbase	in.	63.3		63.3	60		63.0	
	Overall Length (w/ 3pt.)	in.	2WD: 118.1 / 4WD: 114.8		115.0	111		111.4	
	Overall Height (w/ ROPS)	in.	91.7		85.0	82.3		82.3	
	Overall width (min. tread)	in.	55.1		51.4	56.5		46.1	
	Min. ground clearance	in.	2WD: 13.6 / 4WD: 13.4		13.4	13		12.2	
	Min. turning radius w/ brake	ft.	2WD: 7.9 / 4WD: 8.2		8.2	N/A		8.2	
	Weight (w/ROPS)	lbs.	2WD F: 2,480 / 4WD DT: 2,657 / 4WD HST: 2,668		2600	2087		2385	

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.