



Grand L3240 Compact Tractor Implements

Grand L Competitive Optional Implement Comparison

LOADER MODEL		Kubota L3240 LA514 Loader	Kubota L3240 LA724 Loader	John Deere 3320 300CX Loader		New Holland Boomer 30 240TL Loader	
Lift Capacity (Pivot Pin)	lbs.	1351	1865	1,598		1370	
Lift Height (Pivot Pin)	in.	96.4	102	102		97.6	
Reach at Maximum Height	in.	23.3	21.9	15		34	
Boom Breakout Force (Pivot Pin)	lbs.	2835	3404	3325		2925	
Digging Depth at Bucket Level	in.	4.9	4.8	5		8.5	
Cycle Times - Loader Raise	sec.	2.7	3.2	3.57		3.8	
Cycle Times - Loader Lower	sec.	2.2	2.0	2.11		1.7	
Cycle Times - Bucket Dump	sec.	1.3	1.3	3.64		2.2	
Cycle Times - Bucket Rollback	sec.	1.6	1.9	2.15		1.7	
Bucket Angle - Dump Angle	degrees	41	41	44		41.3	
Bucket Angle - Rollback Angle	degrees	30	45	31		30.4	
Quick Attach Coupler		OPTIONAL	OPTIONAL	YES		OPTIONAL	
Quick Attach Loader		YES	YES	YES		YES	
Factory Pallet Forks		YES	YES	YES		N/P	
BACKHOE MODEL		Kubota L3240 BH76 Backhoe	Kubota L3240 BH77 Backhoe	Kubota L3240 BH92 Backhoe	John Deere 3320 48 Backhoe	John Deere 3320 485 Backhoe	New Holland Boomer 30 Backhoe
Digging Depth at 2' flat bottom	in.	91.0	92.5	109.8	92	105	N/P
Swing Arc	degrees	180	180	180	180	180	N/P
Bucket Cylinder Digging Force	lbs.	3339	3421	4548	2840	3730	N/P
Dipperstick Cylinder Digging Force	lbs.	2097	2190	2698	2005	2435	N/P
Loading Height	in.	64.4	67.2	84.3	82	88	N/P
Reach from Swing Point	in.	120.5	124.2	150.4	133	142	N/P
6-Position Hydraulic Thumb		NO	NO	OPTIONAL	NO	NO	N/P
6-Positional Mechanical Thumb		OPTIONAL	OPTIONAL	OPTIONAL	NO	NO	N/P

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.



Grand L3540 Compact Tractor Implements

Grand L Competitive Optional Implement Comparison

LOADER MODEL		Kubota L3540 LA514 Loader	Kubota L3540 LA724 Loader	John Deere 3520 300CX Loader	New Holland Boomer 35 240TL Loader	
Lift Capacity (Pivot Pin)	lbs.	1351	1865	1598	1370	
Lift Height (Pivot Pin)	in.	96.4	102	102	97.6	
Reach at Maximum Height	in.	23.3	21.9	15	34	
Boom Breakout Force (Pivot Pin)	lbs.	2835	3404	3325	2925	
Digging Depth at Bucket Level	in.	4.9	4.8	5	8.5	
Cycle Times - Loader Raise	sec.	2.7	3.2	3.57	3.8	
Cycle Times - Loader Lower	sec.	2.2	2.0	2.11	1.7	
Cycle Times - Bucket Dump	sec.	1.3	1.3	3.64	2.2	
Cycle Times - Bucket Rollback	sec.	1.6	1.9	2.15	1.7	
Bucket Angle - Dump Angle	degrees	41	41	44	41.3	
Bucket Angle - Rollback Angle	degrees	30	45	31	30.4	
Quick Attach Coupler		OPTIONAL	OPTIONAL	YES	OPTIONAL	
Quick Attach Loader		YES	YES	YES	YES	
Factory Pallet Forks		YES	YES	YES	N/P	
BACKHOE MODEL		Kubota L3540 BH76 Backhoe	Kubota L3540 BH77 Backhoe	Kubota L3540 BH92 Backhoe	John Deere 3520 485 Backhoe	New Holland Boomer 35 Backhoe
Digging Depth at 2' flat bottom	in.	91.0	92.5	109.8	105	N/P
Swing Arc	degrees	180	180	180	180	N/P
Bucket Cylinder Digging Force	lbs.	3339	3421	4548	3730	N/P
Dipperstick Cylinder Digging Force	lbs.	2097	2190	2698	2435	N/P
Loading Height	in.	64.4	67.2	84.3	88	N/P
Reach from Swing Point	in.	120.5	124.2	150.4	142	N/P
6-Position Hydraulic Thumb		NO	NO	OPTIONAL	NO	N/P
6-Positional Mechanical Thumb		OPTIONAL	OPTIONAL	OPTIONAL	NO	N/P

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.



Grand L3940 Compact Tractor Implements

Grand L Competitive Optional Implement Comparison							
LOADER MODEL		Kubota L3940 LA724 Loader	John Deere 3520 300CX Loader	John Deere 3720 300CX Loader		New Holland Boomer 40 250TL Loader	
Lift Capacity (Pivot Pin)	lbs.	1865	1,598	1,598		1940	
Lift Height (Pivot Pin)	in.	102	102	102		106.8	
Reach at Maximum Height	in.	21.9	15	15		32	
Boom Breakout Force (Pivot Pin)	lbs.	3404	3325	3325		3470	
Digging Depth at Bucket Level	in.	4.8	5	5		3.0	
Cycle Times - Loader Raise	sec.	3.2	3.57	3.57		4.1	
Cycle Times - Loader Lower	sec.	2.0	2.11	2.11		2.0	
Cycle Times - Bucket Dump	sec.	1.3	3.64	3.64		3.8	
Cycle Times - Bucket Rollback	sec.	1.9	2.15	2.15		2.3	
Bucket Angle - Dump Angle	degrees	41	44	44		51.4	
Bucket Angle - Rollback Angle	degrees	45	31	31		30.3	
Quick Attach Coupler		OPTIONAL	YES	YES		OPTIONAL	
Quick Attach Loader		YES	YES	YES		YES	
Factory Pallet Forks		YES	YES	YES		N/P	
BACKHOE MODEL		Kubota L3940 BH92 Backhoe	John Deere 3520 48 Backhoe	John Deere 3520 485 Backhoe	John Deere 3720 48 Backhoe	John Deere 3720 485 Backhoe	New Holland Boomer 40 Backhoe
Digging Depth at 2' flat bottom	in.	109.8	92	105	92	105	N/P
Swing Arc	degrees	180	180	180	180	180	N/P
Bucket Cylinder Digging Force	lbs.	4548	2840	3730	2840	3730	N/P
Dipperstick Cylinder Digging Force	lbs.	2698	2005	2435	2005	2435	N/P
Loading Height	in.	84.3	82	88	82	88	N/P
Reach from Swing Point	in.	150.4	133	142	133	142	N/P
6-Position Hydraulic Thumb		OPTIONAL	NO	NO	NO	NO	N/P
6-Positional Mechanical Thumb		OPTIONAL	NO	NO	NO	NO	N/P

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.



Grand L4240 Compact Tractor Implements

Grand L Competitive Optional Implement Comparison

LOADER MODEL		Kubota L4240 LA854 Loader	John Deere 3720 300CX Loader	John Deere 4120 400X Loader	New Holland Boomer 50 250TL Loader		
Lift Capacity (Pivot Pin)	lbs.	2489	1598	2346	1940		
Lift Height (Pivot Pin)	in	113	102	112.8	106.8		
Reach at Maximum Height	in.	22.4	15	24.4	32		
Boom Breakout Force (Pivot Pin)	lbs.	4195	3325	3453	3470		
Digging Depth at Bucket Level	in.	6.9	5	6.6	3.0		
Cycle Times - Loader Raise	sec.	4.2	3.57	3.68	4.1		
Cycle Times - Loader Lower	sec.	2.8	2.11	2.48	2.0		
Cycle Times - Bucket Dump	sec.	1.8	3.64	2.44	3.8		
Cycle Times - Bucket Rollback	sec.	2.3	2.15	1.44	2.3		
Bucket Angle - Dump Angle	degrees	45	44	46	51.4		
Bucket Angle - Rollback Angle	degrees	42	31	32	30.3		
Quick Attach Coupler		OPTIONAL	YES	YES	OPTIONAL		
Quick Attach Loader		YES	YES	YES	YES		
Factory Pallet Forks		YES	YES	YES	N/P		
BACKHOE MODEL		Kubota L4240 BH92 Backhoe	John Deere 3720 48 Backhoe	John Deere 3720 485 Backhoe	John Deere 3720 48 Backhoe	John Deere 3720 485 Backhoe	New Holland Boomer 50 Backhoe
Digging Depth at 2' flat bottom	in.	109.8	92	105	92	105	N/P
Swing Arc	degrees	180	180	180	180	180	N/P
Bucket Cylinder Digging Force	lbs.	4548	2840	3730	2840	3730	N/P
Dipperstick Cylinder Digging Force	lbs.	2698	2005	2435	2005	2435	N/P
Loading Height	in.	84.3	82	88	82	88	N/P
Reach from Swing Point	in.	150.4	133	142	133	142	N/P
6-Position Hydraulic Thumb		OPTIONAL	NO	NO	NO	NO	N/P
6-Positional Mechanical Thumb		OPTIONAL	NO	NO	NO	NO	N/P

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.



Grand L4740 Compact Tractor Implements

Grand L Competitive Optional Implement Comparison						
LOADER MODEL		Kubota L4740 LA854 Loader	John Deere 4320 400X Loader		New Holland Boomer 50 250TL Loader	New Holland Boomer 8N 250TL Loader
Lift Capacity (Pivot Pin)	lbs.	2489	2346		1940	2000
Lift Height (Pivot Pin)	in.	113	112.8		106.8	105
Reach at Maximum Height	in.	22.4	24.4		32	33
Boom Breakout Force (Pivot Pin)	lbs.	4195	3453		3470	3540
Digging Depth at Bucket Level	in.	6.9	6.6		3.0	6.5
Cycle Times - Loader Raise	sec.	4.2	3.68		4.1	4.2
Cycle Times - Loader Lower	sec.	2.8	2.48		2.0	3.2
Cycle Times - Bucket Dump	sec.	1.8	2.44		3.8	1.9
Cycle Times - Bucket Rollback	sec.	2.3	1.44		2.3	2.6
Bucket Angle - Dump Angle	degrees	45	46		51.4	58
Bucket Angle - Rollback Angle	degrees	42	32		30.3	30
Quick Attach Coupler		OPTIONAL	YES		OPTIONAL	N/P
Quick Attach Loader		YES	YES		YES	YES
Factory Pallet Forks		YES	YES		N/P	N/P
BACKHOE MODEL		Kubota L4740 BH92 Backhoe	John Deere 4320 48 Backhoe	John Deere 4320 485 Backhoe	New Holland Boomer 50 Backhoe	New Holland Boomer 8N 930GH Backhoe
Digging Depth at 2' flat bottom	in.	109.8	92	105	N/P	102
Swing Arc	degrees	180	180	180	N/P	180
Bucket Cylinder Digging Force	lbs.	4548	2840	3730	N/P	4100
Dipperstick Cylinder Digging Force	lbs.	2698	2005	2435	N/P	2130
Loading Height	in.	84.3	82	88	N/P	N/P
Reach from Swing Point	in.	150.4	133	142	N/P	134
6-Position Hydraulic Thumb		OPTIONAL	NO	NO	N/P	NO
6-Positional Mechanical Thumb		OPTIONAL	NO	NO	N/P	NO

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.



Grand L5040 Compact Tractor Implements

Grand L Competitive Optional Implement Comparison

LOADER MODEL		Kubota L5040 LA854 Loader	John Deere 4520 400X Loader		New Holland Boomer 50 250TL Loader	New Holland Boomer 8N 250TL Loader
Lift Capacity (Pivot Pin)	lbs.	2489	2346		1940	2000
Lift Height (Pivot Pin)	in.	113	112.8		106.8	105
Reach at Maximum Height	in.	22.4	24.4		32	33
Boom Breakout Force (Pivot Pin)	lbs.	4195	3453		3470	3540
Digging Depth at Bucket Level	in.	6.9	6.6		3.0	6.5
Cycle Times - Loader Raise	sec.	4.2	3.68		4.1	4.2
Cycle Times - Loader Lower	sec.	2.8	2.48		2.0	3.2
Cycle Times - Bucket Dump	sec.	1.8	2.44/1.0		3.8	1.9
Cycle Times - Bucket Rollback	sec.	2.3	1.44		2.3	2.6
Bucket Angle - Dump Angle	degrees	45	46		51.4	58
Bucket Angle - Rollback Angle	degrees	42	32		30.3	30
Quick Attach Coupler		OPTIONAL	YES		OPTIONAL	N/P
Quick Attach Loader		YES	YES		YES	YES
Factory Pallet Forks		YES	YES		N/P	N/P
BACKHOE MODEL		Kubota L5040 BH92 Backhoe	John Deere 4520 48 Backhoe	John Deere 4520 485 Backhoe	New Holland Boomer 50 Backhoe	New Holland Boomer 8N 930GH Backhoe
Digging Depth at 2' flat bottom	in.	109.8	92	105	N/P	102
Swing Arc	degrees	180 degrees	180	180	N/P	180
Bucket Cylinder Digging Force	lbs.	4548	2840	3730	N/P	4100
Dipperstick Cylinder Digging Force	lbs.	2698	2005	2435	N/P	2130
Loading Height	in.	84.3	82	88	N/P	N/P
Reach from Swing Point	in.	150.4	133	142	N/P	134
6-Position Hydraulic Thumb		OPTIONAL	NO	NO	N/P	NO
6-Positional Mechanical Thumb		OPTIONAL	NO	NO	N/P	NO

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.



Grand L5240 Compact Tractor Implements

Grand L Competitive Optional Implement Comparison						
LOADER MODEL		Kubota L5240 LA854 Loader	John Deere 4520 400X Loader		New Holland 4055 (T2410) 270TL Loader	
Lift Capacity (Pivot Pin)	lbs.	2489	2346		2500	
Lift Height (Pivot Pin)	in.	113	112.8		112.3	
Reach at Maximum Height	in.	22.4	24.4		32	
Boom Breakout Force (Pivot Pin)	lbs.	4195	3453		5000	
Digging Depth at Bucket Level	in.	6.9	6.6		4.9	
Cycle Times - Loader Raise	sec.	4.2	3.68		4.1	
Cycle Times - Loader Lower	sec.	2.8	2.48		3.9	
Cycle Times - Bucket Dump	sec.	1.8	2.44		4.1	
Cycle Times - Bucket Rollback	sec.	2.3	1.44		3.2	
Bucket Angle - Dump Angle	degrees	45	46		49	
Bucket Angle - Rollback Angle	degrees	42	32		39	
Quick Attach Coupler		OPTIONAL	YES		OPTIONAL	
Quick Attach Loader		YES	YES		YES	
Factory Pallet Forks		YES	YES		YES	
BACKHOE MODEL		Kubota L5240 BH92 Backhoe	John Deere 4520 48 Backhoe	John Deere 4520 485 Backhoe	New Holland 4055 (T2410) 930GH Backhoe	New Holland 4055 (T2410) 940GH Backhoe
Digging Depth at 2' flat bottom	in.	109.8	92	105	102	113.5
Swing Arc	degrees	180	180	180	180	180
Bucket Cylinder Digging Force	lbs.	4548	2840	3730	4100	4100
Dipperstick Cylinder Digging Force	lbs.	2698	2005	2435	2130	2670
Loading Height	in.	84.3	82	88	N/P	N/P
Reach from Swing Point	in.	150.4	133	142	134	149
6-Position Hydraulic Thumb		OPTIONAL	NO	NO	NO	NO
6-Positional Mechanical Thumb		OPTIONAL	NO	NO	NO	NO

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.



Grand L5740 Compact Tractor Implements

Grand L Competitive Optional Implement Comparison						
LOADER MODEL		Kubota L5740 LA854 Loader	John Deere 4720 400X Loader	New Holland 4060 (T2420) 250TL Loader	New Holland 4060 (T2420) 270TL Loader	
Lift Capacity (Pivot Pin)	lbs.	2489	2346	2000	2500	
Lift Height (Pivot Pin)	in.	113	112.8	105	112.3	
Reach at Maximum Height	in.	22.4	24.4	33	32	
Boom Breakout Force (Pivot Pin)	lbs.	4195	3453	3540	5000	
Digging Depth at Bucket Level	in.	6.9	6.6	6.5	4.9	
Cycle Times - Loader Raise	sec.	4.2	3.68	4.2	4.1	
Cycle Times - Loader Lower	sec.	2.8	2.48	3.2	3.9	
Cycle Times - Bucket Dump	sec.	1.8	2.44/1.0	1.9	4.1	
Cycle Times - Bucket Rollback	sec.	2.3	1.44	2.6	3.2	
Bucket Angle - Dump Angle	degrees	45	46	58	49	
Bucket Angle - Rollback Angle	degrees	42	32	30	39	
Quick Attach Coupler		OPTIONAL	YES	OPTIONAL	OPTIONAL	
Quick Attach Loader		YES	YES	YES	YES	
Factory Pallet Forks		YES	YES	YES	YES	
BACKHOE MODEL		Kubota L5740 BH92 Backhoe	John Deere 4720 48 Backhoe	New Holland 4060 (T2420) 920GH Backhoe	New Holland 4060 (T2420) 930GH Backhoe	New Holland 4060 (T2420) 940GH Backhoe
Digging Depth at 2' flat bottom	in.	109.8	92	89.9	102	113.5
Swing Arc	degrees	180	180	180	180	180
Bucket Cylinder Digging Force	lbs.	4548	2840	2785	4100	4100
Dipperstick Cylinder Digging Force	lbs.	2698	2005	2020	2130	2670
Loading Height	in.	84.3	82	N/P	N/P	N/P
Reach from Swing Point	in.	150.4	133	123	134	149
6-Position Hydraulic Thumb		OPTIONAL	NO	NO	NO	NO
6-Positional Mechanical Thumb		OPTIONAL	NO	NO	NO	NO

N/A = Not Available

N/P = Not Published

This comparison of specifications is based upon the most reliable information obtained by Kubota at the time of publication. It is correct to the best of our knowledge. Kubota reserves the right to change the specifications relating to its products without notice.