



RTV1140CPX Utility Vehicles

Competitive Comparison

MODEL		KUBOTA RTV1140CPX	KAWASAKI 4010 Mule Trans4x4 Diesel	POLARIS RANGER CREW 4X4 EFI
Engine	Make	Kubota	Daihatsu	Robin
	Type	4-cycle diesel	4-cycle diesel	4-cycle gas
	Cylinders	3	3	2
	Displacement (cc)	1123	953	683
	Horsepower	24.8hp @ 3000 rpm	24.7hp @ 3600 rpm	40 hp
	Max Torque (ft-lbs)	50.6	--	--
Fuel Tank Capacity		7.9 gallons	6.4 gallons	9.0 gallons
Muffler		Spark arresting	Spark arresting	Spark arresting
Alternator		60 amps	40 amps	500 watts
Transmission	Type	Variable Hydrostatic Transmission (VHT Plus)	CVT with belts	CVT with belts
	Wheels, drive system	Rear 2WD or 4WD	Rear 2WD or 4WD	Rear 2WD or 4WD
	Differential Lock	Standard, foot operated	Rear, dual-mode	Front- on/off switch Rear-hand operated
	Gear Selection	Hi-Med-Lo range forward, neutral, reverse	Hi Lo range forward, neutral, reverse	Hi-Lo range forward, neutral, reverse
Steering		Power	Power	Manual
Brakes	Front	Sealed hydraulic discs	hydraulic drums	hydraulic disc
	Rear	Sealed hydraulic discs	hydraulic drums	hydraulic disc
	Parking	rear wheel, hand lever	rear wheel, hand lever	rear wheel, hand lever
Suspension	Front	Independent, McPherson struts	Independent, McPherson struts	Independent, McPherson struts
	Rear	Semi-independent DeDion axle w/ leaf springs and hydraulic shocks	Semi-independent DeDion axle w/ leaf springs and hydraulic shocks	Independent
Rollover Protection System		2.0" steel tube; meets OSHA 1928.53 & SAE J2194 ROPS	meets OSHA 1928.53 & SAE J2194 ROPS	N/A
Overall Dimensions (in inches)	Length	137.0	130.1	145.0
	Width	60.8	58.5	60.0
	Height, overall	79.5	75.8	75.0
	Wheelbase	95.1	85.2	108.0
	Ground clearance, front axle	7.7	7.1	8.0
	Ground clearance, rear axle	7.5	7.1	9.0
Turning radius (ft)		15.7	12.8	18.5
Payload Capacity (lbs)		1642	1632	1750
Towing Capacity (lbs)		1300	1200	2000
Vehicle weight (lbs)		2360	1737	1460.0
Cargo Bed	Bed Load Capacity (lbs) 1-row or 2-row mode	1102 or 661	800 or 400	1000
	Bed Lift System	hydraulic	manual	manual
	Width x Length x Depth (inches) -- 1 row mode	52.0 x 53.5 x 11.4	47.7 x 50.4 x 11.3	n/a
	Width x Length x Depth (inches) -- 2 row mode	52.0 x 33.9 x 11.4	47.7 x 30.3 x 11.3	56 x 36.5 x 11.5
	Volume (cu ft) 1 or 2 row	18.4 or 11.7	15.6 or 9.4	13.2
Tires	Front	25x10-12	23x11-10	26x9-12
	Rear	25x10-12	23x11-10	26x11-12

N/A = Not Available

N/P = Not Published

These comparisons of specifications are based on the most reliable data available to Kubota at the time of publication.

Kubota reserves the right to change specifications relating to its products without notice.

Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was being prepared. It is correct to the best of our knowledge.