



B26 Loader/Landscaper Tractors (TLB)

Competitive Comparison						
MODEL		Kubota B26 TLB	Allmand TLB - 425 ESL	JCB Mini CX	Terramite T7	
Engine	Engine gross power	hp	26.0	25	22.5	26
	PTO power	hp	19.5	No PTO	No PTO	No PTO
	No. of cylinders		3	3	3	3
	Total displacement	cu. in.	68.5	68.5	69	INA
	Fuel tank capacity	gal.	8.2	12	6.4	9.5
Transmission	Type		HST (3 ranges)	HST (1 range)	HST (1 range)	HST (1 range)
	4 Wheel Drive		Standard	No	Standard	No
	Maximum Travel Speed	mph	11.2	5.5	6.2	INA
	Brake		Multi Wet Disc	Hydrostatic	Multi Wet Disc	INA
PTO	Standard		Rear	No PTO	No PTO	No PTO
	Speeds @ RPM		540 @ 2768	N/A	N/A	N/A
	Control		Hydraulic Independent	N/A	N/A	N/A
Tires	R4	Front	23 x 8.50 - 14	23 x 10.5 - 12	23 x 8.5 x 12	23 x 10.5 - 12
		Rear	12.4 - 16	31 x 15.5 - 15	31 x 15.5 x 15	31 x 15.5 - 15
	Ag	Front	23 x 8.50 - 14	N/A	N/A	N/A
		Rear	12.4 - 16	N/A	N/A	Available
	Turf	Front	24x 8.50 - 14	N/A	23 x 8.5 x 12	Available
		Rear	13.6 - 16	N/A	31 x 15.5 x 15	Available
Hydraulic System	Pump capacity	gpm	11.2	INA	6.3	7
	3-Point Hitch lift capacity @ 24" behind lift point	lbs.	1676	No 3-Point Hitch	No 3-Point Hitch	No 3-Point Hitch
	Position Control		Standard	N/A	N/A	N/A
	Power steering		Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Loader	Loader Quick Coupler		Standard	N/A	Optional	N/A
	Loader Bucket Capacity	cu. ft.	9.5	8.8	8.8	8.9
	Auxiliary Hydraulic Flow	gpm	7.0	8.0	8.45	7.0
	Breakout Force	lbs.	3967	3400	3607	4400
	Lift Capacity	lbs.	1300	2100	1378	1700
	Protected Hoses		Standard	N/A	Standard	N/A
	Mechanical Spill Guard		Standard	N/A	N/A	N/A
	Side Position Lever w/ Arm Rest		Standard	N/A	No Arm Rest	N/A
Backhoe	Quick Attach Backhoe		Standard	No	No	No
	Maximim Digging Depth		8' 4"	8' 4"	8' 4"	8' 8"
	Bucket Breakout Force	lbs.	4,211	2,875	2,884	3100
	Dipper Breakout Force	lbs.	2,123	2,265	2,171	2800
	Auxiliary Hydraulic Flow	gpm	7.0	N/A	8.45	N/A
	Arch Type Boom		Standard	N/A	Standard	Standard
	Bucket QC Option		Available	N/A	N/A	Available
	Thumb Option		Available	N/A	N/A	N/A
Features	ROPS / FOPS Canopy		Standard	4 - Post ROPS	Standard	4 - Post ROPS
	Side Position Throttle & Key		Standard	N/A	INA	N/A
	Turn In Place Seat		Standard	N/A	Standard	N/A
	Tilt Steering Wheel		Standard	N/A	INA	N/A
	Retractable Seat Belt		Standard	N/A	INA	N/A
	Spark Arrestor Muffler		Standard	INA	INA	INA
Dimensions	Wheelbase	in.	62.2	65	6.2	58
	Min. ground clearance	in.	11.3	11	INA	INA
	Transport Length	in.	198	163	188	177
	Overall height	in.	89.5	84.5	85	82
	Overall width	in.	60	56	59	58
	Weight	lbs.	4,001	4,320	4321	4,125

These comparison of specifications are based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice. Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was being prepared. It is correct to the best of our knowledge but due to technological developments it is subject to change without notice.