

ITEM	GREASE POINTS	CAPACITY	TYPE OF GREASE
FRONT WHEEL HUBS	2 (2WD only)	A small amount	Bearing Grease
KNUCKLE SHAFT	2 (2WD only)	Until Grease Overflows	SAE Multi-Purpose Type Grease
CLUTCH PEDAL	1	Until Grease Overflows	SAE Multi-Purpose Type Grease
BRAKE PEDAL	1	Until Grease Overflows	SAE Multi-Purpose Type Grease
PEDAL SHAFT SUPPORT	1	Until Grease Overflows	SAE Multi-Purpose Type Grease
TOP LINK	2	Until Grease Overflows	SAE Multi-Purpose Type Grease
TOP LINK BRACKET	3	Until Grease Overflows	SAE Multi-Purpose Type Grease
HANDLE POST	3	Until Grease Overflows	SAE Multi-Purpose Type Grease
LIFT ROD	1	Until Grease Overflows	SAE Multi-Purpose Type Grease
BATTERY TERMINAL	2	Cover terminals with a thin film	Non-Conductive Grease
CLUTCH RELEASE HUB	1	Grease when assembled	SAE Multi-Purpose Type Grease

Notes:

- Transmission Fluid:
 - KUBOTA Super Universal Dynamic Tractor Fluid (SUPER UDT) is the original and recommended transmission hydraulic fluid.
 - The fluid used to lubricate the transmission is also used as the operating hydraulic fluid. To ensure proper operation of the hydraulic system and complete lubrication of the transmission, we recommend the use of KUBOTA UDT or SUPER UDT fluid for optimum protection and performance. (Consult your KUBOTA dealer for further details.)