Kubota

Compact Tractors
L2800 / L3400 / L4400

COMPARISON

FEATURES	KUBOTA L2800		KUBOTA L3400		JOHN DEERE 790	JOHN DEERE 3203	NEW HOLLAND TC30	
	GEAR 2WD/4WD	HST 4WD	GEAR 2WD/4WD	HST 4WD	GEAR 2WD/4WD	HST 4WD	GEAR 2WD/4WD	HST 4WD
Engine								
Engine Manufacturer	Kubota	Kubota	Kubota	Kubota	Yanmar	Yanmar	Shibaura	Shibaura
Gross HP (kw) @ Rated RPM	29.0 (21.6)	29.0 (21.6)	34.7 (25.9)	34.7 (25.9)	27.0 (20.1)	32.1 (23.9)	30.0 (22.4)	30.0 (22.4)
PTO HP (kw) @ Rated RPM	24.0 (17.9)	22.5 (16.8)	29.0 (21.6)	27.5 (20.5)	24.0 (17.6)	24.0 (17.9)	25.5 (19.0)	24 (17.9)
Rated Speed (RPM)	2800	2800	2700	2700	2600	2800	2600	2600
Displacement cu in(cu cm)	85.0 (1393)	85.0 (1393)	85.0 (1393)	85.0 (1393)	81.2 (1331)	91.3 (1496)	91.3 (1496)	91.3 (1496)
Cylinders	3	3	3	3	3	3	3	3
Fuel Tank Capacity gal(l)	9.0 (34.0)	9.0 (34.0)	9.0 (34.0)	9.0 (34.0)	6.3 (24)	11.5 (43.5)	7.1 (27)	7.1 (27)
Air Cleaner	Single Element (Dual Optional)	Single Element (Dual Optional)	Single Element (Dual Optional)	Single Element (Dual Optional)	Dual Element	Dual Element	Dual Element	Dual Element
Transmission / Drive Train								
Transmission	Sliding Gear and Constant Mesh	Hydrostatic	Sliding Gear and Constant Mesh	Hydrostatic	Sliding Gear	Hydrostatic	Info N/A	Hydrostatic
Gear Transmission Speeds	8F / 4R	N/A	8F / 4R	N/A	8F / 2R	N/A	9F / 3R	N/A
Hydrostatic Speed Ranges	N/A	3 Range	N/A	3 Range	N/A	2 Range	N/A	3 Range
Brakes	Multiple Wet Disks	Multiple Wet Disks	Multiple Wet Disks	Multiple Wet Disks	Dry Shoe	Wet Disk	Wet Disk	Wet Disk
Travel Speeds @ rated RPM mph(km/h)	F 1.1(1.8)-13.7(22.0) R 1.5(2.4)-4.9(7.9)	F 0(0)-14.7(23.6) R 0(0)-13.2(21.2)	F 1.1(1.8)-13.2(21.2) R 1.5(2.4)-4.7(7.6)	F 0(0)-14.1(22.7) R 0(0)-12.7(20.5)	F 11.8(18.9) R 3.4(5.5)	F 12.9(20.8) R 12.5(20.2)	F 0.75(1.21)-12.9(20.8)	F 0(0)-14.5(23.3)

Kubota

Compact Tractors
L2800 / L3400 / L4400

COMPARISON

FEATURES	KUBOTA L2800		KUBOTA L3400		JOHN DEERE 790	JOHN DEERE 3203	NEW HOLLAND TC30	
Transmission / Drive Train Continued								
Clutch 2WD/4WD	Dry Type Single Stage	Dry Type Single Stage	Dry Type Dual Stage	Dry Type Single Stage	DryType-Single Stage/ Dry Type-Dual Stage	Wet Disk	Dry Type Single Stage	Dry Type Single Stage
PTO System								
Type 2WD/4WD	Trans. Driven w/ORC	Live-Cont. Running	Live-Cont. Running	Live-Cont. Running	Transmission Driven	Independent	Trans. Driven With ORC/Live Cont.	Live-Cont.
Rear PTO	540	540	540	540	540	540	540	540
Mid PTO	N/A	N/A	N/A	N/A	Opt 2100	N/A	Opt 2000	Std 2000
Hydraulic System								
Hitch Category (SAE)	Category 1	Category 1	Category 1	Category 1	Category 1	Category 1	Category 1	Category 1
Lift Control Type	Position Control	Position Control	Position Control	Position Control	Position Control	Position Control	Position Control	Position Control
Pump Capacity (main/PS) gpm(l/m)	6.5(24.7)/ 4.0(15.0)	6.5(24.7)/ 4.0(15.0)	6.3(23.9)/ 3.8(14.5)	6.3(23.9)/ 3.8(14.5)	5.6(21.1)/ 4.3(16.3)	5.7(21.6)/ 7.6(28.8)	6.1(23.0)/ 3.5(13.2)	6.1(23.0)/ 3.5(13.2)
Lift Capacity @ Lift Point lbs(kg)	1998(906)	1998(906)	1998(906)	1998(906)	Info N/A	Info N/A	1635(743)	1635(743)
Lift Capacity @ 24" Behind Lift Point lbs(kg)	1435(651)	1435(651)	1435(651)	1435(651)	815(370)	1868(849)	Info N/A	Info N/A
Power Steering 2WD/4WD	Hydrostatic	Integral Hydraulic	Hydrostatic	Integral Hydraulic	Manual/ Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic

Kubota

L Compact Tractors
L2800 / L3400 / L4400

COMPARISON

FEATURES	KUBOTA L2800		KUBOTA L3400		JOHN DEERE 790	JOHN DEERE 3203	NEW HOLLAND TC30	
Dimensions								
Wheelbase in(mm)	63.3(1610)	63.3(1610)	63.3(1610)	63.3(1610)	61.0(1550)	68.0(1730)	63.0(1600)	63.0(1600)
Overall Length (without 3-pt hitch) 2WD/4WD in.(mm)	110.0(2810)/ 106.5(2705)	106.5(2705)	110.0(2810)/ 106.5(2705)	106.5(2705)	112.3(2852) With 3-Pt Hitch	120.2(3050) With 3-Pt Hitch	108.9(2765)	108.9(2765)
Overall Width (min. tread) in(mm)	51.4(1305)	51.4(1305)	51.4(1305)	51.4(1305)	57.2(1453)	53.1(1350)	54.3(1380)	54.3(1380)
Overall Ht. (w/ROPS) in.(mm)	85.0(2160)	85.0(2160)	85.0(2160)	85.0(2160)	82.3(2090)	83.8(2130)	82.4(2093)	82.4(2093)
Weight 2WD/4WD (inc. std. tires and ROPS lbs(kg)	2359(1070)/ 2536(1150)	2600(1180)	2403(1090)/ 2580(1170)	2600(1180)	1930(875)/ 2150(955)	2700(1227)	2WD 2193(995)	Info N/A
Tread (front) 2WD/4WD in(mm)	41.3(1050)/ 43.1(1095)	43.1(1095)	41.3(1050)/ 43.1(1095)	43.1(1095)	Info N/A	Info N/A	Info N/A	Info N/A
Tread (rear) 2WD/4WD in.(mm)	40.2(1020), 43.8(1115), 47.1(1195), 50.8(1290)	40.2(1020), 43.8(1115), 47.1(1195), 50.8(1290)	40.2(1020), 43.8(1115), 47.1(1195), 50.8(1290)	40.2(1020), 43.8(1115), 47.1(1195), 50.8(1290)	Info N/A	Info N/A	Info N/A	Info N/A
Min. Clearance 2WD/4WD in(mm)	13.6(345)/ 13.4(340)	13.4(340)	13.6(345)/ 13.4(340)	13.4(340)	16.1(409)	Info N/A	12.0(305)	Info N/A
Tires - Standard								
Front 2WD/4WD	5.0-15/7.0-16	7.0-16	5.0-15/7.0-16	7.0-16	5.0-15/7.0-14	15.0-19.5	5.5-16	5.5-16
Rear	11.2-24	11.2-24	11.2-24	11.2-24	11.2-24	25x8.5-14	11.2-24	11.2-24

Kubota

Compact Tractors
L2800 / L3400 / L4400

COMPARISON

FEATURES	KUBOTA L2800		KUBOTA L3400		JOHN DEERE 790	JOHN DEERE 3203	NEW HOLLAND TC30	
Other								
Deck	Semi-Flat Deck	Semi-Flat Deck	Semi-Flat Deck	Semi-Flat Deck	Straddle Deck	Flat	Semi-Flat Deck	Semi-Flat Deck
Foldable ROPS	Opt	Opt	Opt	Opt	N/A	N/A	N/A	N/A
Min. Turning Radius 2WD/4WD ft(m)	7.9(2.4)/8.2(2.5)	8.2(2.5	7.9(2.4)/8.2(2.5)	8.2(2.5	7.0(2.1)/7.0(2.1)	Info N/A	Info N/A	Info N/A
Cruise Control	N/A	Std - Mechanical	N/A	Std - Mechanical	N/A	N/A	N/A	Opt - Electric
Alternator Amps	40	40	40	40	20	75	40	40
Rear Differential Lock	Std	Std	Std	Std	Std	Std	Std	Std
Under Hood Muffler	Std	Std	Std	Std	No	Std	Std	Std

This comparison of specifications is based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice. Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was prepared. It is correct to the best of our knowledge, but due to technological developments, it is subject to change without notice.