


COMPARISON

FEATURE	KUBOTA L5030		JOHN DEERE 4520
Engine			
Engine Manufacturer/Model		Kubota V2403	JD 4024T
Gross Horsepower	HP	52.2	58.0
PTO Horsepower	HP	44.0 Gear or 42.5 Hydro	50.0
Rated Speed	RPM	2700	2400
No. Cylinders/Displacement	cu. in.	4 / 148.5	4 / 149
Fuel Tank Capacity	gal.	11.4	14.5
Air Cleaner		Dual Element	Dual Element
Dimensions			
Wheelbase	in.	75.4	71.5
Overall Length (w/out 3-pt hitch)	in.	126.2	Info Not Available
Overall Width (min. tread)	in.	67.3	Info Not Available
Overall Height (top of ROPS)	in.	86.2	Info Not Available
Weight (inc. std. tires and ROPS)	lbs.	3705 Gear or 3745 Hydro	3700
Min. Ground Clearance	in.	15.7	Info Not Available
Transmission / Drive Train			
Transmission		Synchronized Shuttle or Hydrostatic	Hydrostatic
Manual Speeds		12F/8R, or 3 Range Hydro	3 Range Hydro
Creep Speed		Optional (Gear-Drive Only)	Not Available
Brakes		Multiple Wet Disc	Wet Disc
Clutch		Dry Type - Single Stage	Wet Disc
PTO System			
Type		Independent	Independent
Rear PTO	RPM	540	540
Mid PTO	RPM	Optional 2000	Optional 2100
Hydraulic System / 3-Point Hitch			
Hitch Category (SAE)		Category I	Category I
3-Point Linkage		Telescopic Stabilizers AND Telescopic Lower Links	Telescopic Stabilizers Only
Pump Capacity (Main/PS)	gpm	9.8 / 4.9	12 / 5.1



COMPARISON			
FEATURE		KUBOTA L5030	JOHN DEERE 4520
Lift Capacity at 24" Behind L.P.	lbs.	2980	2500
Draft Control/Top-n-Tilt Kit		Optional / Optional	Not Available / Optional
Steering		Hydrostatic	Power
Standard Tires			
Front Tire		9.5-16	8-16
Rear Tire		14.9-26	13.6-28
Other Specifications			
Deck		Flat	Flat
Min. Turning Radius	ft.	9.2	9.2
Cruise Control		Standard	Optional
Alternator	amps	45 (60 on Cab Models)	75
Rear Differential Lock		Standard	Standard
Entry/Exit Step		Standard	Standard
Drawbar		Adj. Drawbar Std / Swinging Optional	Adjustable Drawbar
Foldable ROPS		Optional (No Charge)	Standard
Tilt Steering Wheel		Standard	Standard
Tool Box		Standard	Standard
Cup Holder		Standard	Standard
Deluxe Seat with Armrests		Standard	Armrests Optional
Rubber Mat		Standard	Standard
Underhood Muffler		Standard	Standard

This comparison of specifications is based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice. Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was prepared. It is correct to the best of our knowledge, but due to technological developments, it is subject to change without notice.