



SPECIFICATIONS

| MODEL | | L5030 | | | |
|--------------------|---|--|----------------------------|-------------|--|
| | | GST (4WD) | GST (4WD) | HST (4WD) | |
| Engine | Type | E-TVCS, indirect injection, vertical, liquid-cooled 4-cycle diesel | | | |
| | Engine gross power | HP (kW) | 52.2 (38.9) | | |
| | Engine net power | HP (kW) | 50.0 (37.5) | | |
| | PTO power | HP (kW) | 44.0 (33.0) | 42.5 (31.8) | |
| | No. of cylinders | | 4 | | |
| | Bore & stroke | in. (mm) | 3.4 x 4.0 (87 x 102.4) | | |
| | Total displace | cu.in. (cc) | 148.6 (2434) | | |
| | Rated speed | rpm | 2700 | | |
| | Battery | | 80D 26R, 12V | | |
| | Alternator | | 12V, 45A | 12V, 60A | |
| | Fuel tank capacity | US gal. (L) | 11.4 (43) | | |
| PTO | Rear PTO | | | | |
| | Revolution | | 1 speed: 540 rpm | | |
| | Type | Independent | Independent ^{*2)} | | |
| | Mid PTO | | Option | | |
| Hydraulic | Revolution | | 1 speed: 2000 rpm | | |
| | Lift control type: Position | | Standard | | |
| | Draft | | Option | | |
| | Implement pump | GPM (L/min.) | 9.8 (37.0) | | |
| | Power steering pump | GPM (L/min.) | 4.9 (18.6) | | |
| | Total hydraulic flow | GPM (L/min.) | 14.7 (55.6) | | |
| 3-point hitch | | Category I & II | | | |
| | Lift capacity at 24 in. behind lift point | lbs. (kg) | 2980 (1350) | | |
| Traveling System | Transmission | GST 12F / 8R | HST (3 Ranges) | | |
| | Steering | Hydrostatic power steering | | | |
| | Brake | Wet disc type | | | |
| | Clutch | Dry type single stage | | | |
| Std. tire size *1) | Front | 9.5 - 16 | | | |
| | Rear | 14.9 - 26 | | | |

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only.

Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

*1) Kubota offers several tire options.

*2) With Master Clutch.

*3) Speeds 3,5,7 and 9 of the GST are not included in the FST's 8 forward speeds.



SPECIFICATIONS

| MODEL | | L5030 | | | | | | | |
|---|---------------------------------------|------------------------|-------------|--|-------------------------|------------------------|-------------|--|--|
| | | GST (4WD) | | GST (4WD) | | HST (4WD) | | | |
| Travel speeds | No. of speeds (at rated engine speed) | GST ^{*3)} | | Optional creep speeds for GST ^{*3)} | | HST | | | |
| | mph (km/h) | 12 Forward / 8 Reverse | | 12 Forward /8 Reverse | | 3 Ranges | | | |
| | | Forward | Reverse | Forward | Reverse | Forward | | | |
| | First | 1.0 (1.6) | 0.9 (1.5) | 0.11 (0.17) | 0.10 (0.17) | Low: | | | |
| | Second | 1.4 (2.3) | 1.3 (2.2) | 0.15 (0.25) | 0.15 (0.24) | L: 0 (0) to 3.8 (6.1) | | | |
| | Third | 1.8 (3.0) | 2.1 (3.5) | 0.21 (0.33) | 0.24 (0.38) | Medium: | | | |
| | Fourth | 2.2 (3.6) | 3.1 (5.1) | 0.25 (0.40) | 0.35 (0.57) | M: 0 (0) to 7.3 (11.8) | | | |
| | Fifth | 2.7 (4.4) | 4.6 (7.5) | 0.31 (0.49) | 0.52 (0.84) | High: | | | |
| | Sixth | 3.3 (5.3) | 6.6 (10.7) | 0.37 (0.59) | 0.74 (1.19) | H: 0 (0) to16.2 (26.1) | | | |
| | Seventh | 4.0 (6.5) | 10.6 (17.1) | 0.45 (0.73) | 1.20 (1.93) | Reverse | | | |
| | Eighth | 4.9 (7.8) | 15.7 (25.4) | 0.55 (0.88) | 1.77 (2.85) | Low: | | | |
| | Ninth | 5.7 (9.2) | | 0.64 (1.03) | | L: 0 (0) to 3.4 (5.5) | | | |
| | Tenth | 6.9 (11.1) | | 0.77 (1.24) | | Medium: | | | |
| Eleventh | 11.1(17.9) | | 1.26 (2.02) | | M: 0 (0) to 6.6 (10.7) | | | | |
| Twelfth | 16.5 (26.6) | | 1.85 (2.98) | | High: | | | | |
| | | | | | H: 0 (0) to 14.6 (23.5) | | | | |
| Dimensions | Overall length (w/o 3P) | in. (mm) | | 126.2 (3205) | | | | | |
| | Overall width (min. tread) | in. (mm) | | 67.3 (1710) | | | | | |
| | Overall height (w/ROPS) | in. (mm) | | 92.7 / 86.2 (2355 / 2190) | | 89.4 (2270) | | | |
| | Wheelbase | in. (mm) | | 75.4 (1915) | | | | | |
| | Min. ground clearance | in. (mm) | | 15.9 (405) | | | | | |
| | Front Tread | (Front tire) | in. (mm) | | 52.8 (1340) | | | | |
| | Rear Tread | (Rear tire) | in. (mm) | | 52.2 (1325) | | 56.3 (1410) | | |
| Min. turning radius (w/brake, 4WD disengaged) | feet (m) | | 9.8 (3.0) | | | | | | |
| Weight (with ROPS) | lbs. (kg) | | 3705 (1680) | | 3745 (1700) | | 4090 (1855) | | |

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only.

Please contact your local Kubota dealer for warranty information.

For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

*1) Kubota offers several tire options.

*2) With Master Clutch.

*3) Speeds 3,5,7 and 9 of the GST are not included in the FST's 8 forward speeds.