



B Compact Tractors
B7800



Competitive Comparison					
MODEL		Kubota B7800HSD	New Holland T1510HST		
Engine	Engine gross power	HP(kw)	30 (22.3)	30 (22.4)	
	PTO power	HP(kw)	22 (16.4)	24.0 (17.9)	
	No. of cylinders		4	3	
	Total displacement	cu.in.(cm3)	91.5 (1498)	91.3 (1496)	
	Fuel tank capacity	gal.(l)	6.9 (26)	7.1 (27)	
	Double air cleaner		Standard	Standard	
Drive Train	Transmission		HST (3 range)	HST (3 range)	
	Max. traveling speed	mph(km/h)	11.9 (19.1)	13.6 (21.9)	
	Brake		Wet, Disc	Wet, Disc	
PTO	Live PTO		Standard	N/P	
	Independent PTO		N/A	Standard	
	Mid PTO		Standard	Standard	
Tires	Farm	Front	7-12	5.50 x 16	
		Rear	12.4-16	11.2 x 24	
	Turf	Front	24x8.50-14	23 x 8.50-12	
		Rear	13.6-16	13.6 x 16	
	R4	Front	23-8.50-14	N/P	
		Rear	12.4-16	N/P	
Hydraulic System	Pump capacity	gpm(l/min)	9.6 (36.1)	6.2+3.8 (23.3+14.2)	
	3-Point Hitch lift capacity @ 24" behind lift point	lbs.(kg)	1300(590)	1635 (743)	
	Position control		Standard	Standard	
	Power steering		Hydrostatic Power Steering	Hydrostatic Power Steering	
3-Point Hitch	Telescopic lower link ends		N/A	N/P	
	Lift rod adjustment		Crank	N/P	
Generals	Cup Holder		N/A	N/P	
	Toolbox		Standard	N/P	
Dimensions	Wheelbase	in.(mm)	65.6 (1666)	63.0 (1600)	
	Tread	Front	in.(mm)	36.8 (935)	N/P
		Rear	in.(mm)	41.3 (1050)	N/P
	Min. ground clearance	in.(mm)	14.6 (370)	N/P	
	Overall length w/3-Point Hitch	in.(mm)	109.4 (2780)	N/P	
	Overall height	in.(mm)	88.9 (2258)	82.3 (2090)	
	Overall width	in.(mm)	53.8 (1366)	62 (1575)	
Weight (w/ROPS)	lbs.(kg)	1740 (790)	2385 (1082)		

N/A = Not Available
N/P = Not Published

These comparison of specifications are based upon the most reliable data obtained by Kubota at the time of publication. Kubota reserves the right to change the specifications relating to its products without notice.

Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was being prepared. It is correct to the best of our knowledge.