

# B

## B2630/B3030

# OTHERS



### Mid Mount Mowers

- Features a generous 60" or 72" cutting path.
- Each deck features a right-hand discharge and is compatible with the front loader.
- Cutting height can be adjusted from 1.5" to 4.0" in ½" increments.
- Easy on/off, quick attach linkage that allows a quick detach the mower, with no need for tools.
- Floating deck design



### Front Mounted Snow Blower

- Available in both 51" and 63"
- Female Quick Hitch
- Half PTO Driveline
- Adjustable Skid Shoes
- Replaceable Cutting Edge
- Manual or Hydraulic Chute Rotation
- Manual or Electric Chute Deflector.
- Drift Cutter Extensions



### Front Mounted Rotary Sweeper

- Front implement system which utilizes a single quick hitch and subframe
- 56.5" maximum sweeping width
- Hydraulic angling
- Adjustable suspension
- Mid PTO drive system
- Parking stands
- Optional side caster wheels for lawn dethatching
- Optional rubber dust deflector



### Front Mounted Blade

- 60" and 72" front blade.
- Front implement system which utilizes a single quick hitch and subframe
- Front Blade is a heavy duty blade designed for commercial use.
- Hydraulic power angle is a standard feature on the 60" Front Blade.
- HD double bevel cutting edge
- Replaceable skid shoes
- Trip spring lockout design
- Optional rubber cutting edge



### Rotary Tillers

- Available in both 40" and 50"
- Built-in slip clutch for system protection
- Spring loaded rear shield for smoother ground cover.
- Gear box and frame are a one unit assembly for greater durability
- CAT. 1, 3-point Hitch

# B

## B2630/B3030

### OTHERS



#### Ballast Box

- Mounted on the three point hitch with sand or gravel to counter balance the tractor when operating with a front implement.
- Holds a maximum of 400 lbs. (182 kg) of dry sand.
- The total weight of the ballast box with sand is 500 lbs. (227 kg).
- The maximum weight allowed on the three point hitch of a B-Series tractor is 500 lbs. (227 kg).
- Ballast is required in loader applications.



#### Rear Mounted Snowblower

- 51" or 64" Cutting Width 2-stage snowblower
- Replaceable Cutting Edge
- Optional Manual or Hydraulic Chute Rotation Kits Available
- Optional Hydraulic Chute Deflector or Electric Chute Deflector
- Optional drift cutter extensions (Increases cutting width by 5")

#### Grass Catcher

- Total collection capacity 9.75 bushels (3 grass bags)
- Impeller 6 blade, 13.5" diameter
- Impeller speed 2160 rpm
- Impeller powered by tractor rear PTO