

B**B2630/B3030****Kubota****SPECIFICATIONS****Specifications**

| Model | | B2630HSD | B3030HSD | B3030HSDC |
|---|-------------------------|--|-----------------------------|-----------------------|
| Engine | | E-TVCS, liquid cooled, 3-cylinder diesel | | |
| Type | | E-TVCS, liquid cooled, 4-cylinder diesel | | |
| Make, Model | | Kubota D1105-E3-D21 | Kubota V1505-E3-D21 | Kubota V1505-E3-D21-Q |
| PTO horsepower | HP (kW) | 19.5 (14.5) | 23.0 (17.1) | 23.0 (17.1) |
| Engine gross horsepower | HP (kW) | 26.0 (19.4) | 30.0 (22.3) | 30.0 (22.3) |
| Rated RPM | rpm | 2800 rpm | 2600 rpm | 2600 rpm |
| Bore and stroke | in. (mm) | 3.1×3.1 (78×78.4) | 3.1×3.1 (78×78.4) | 3.1×3.1 (78×78.4) |
| Displacement | cu. in. (cc) | 68.5 (1123) | 91.5 (1498) | 91.5 (1498) |
| Air cleaner | | Dual paper element | | |
| Lubrication | | Forced lubrication | | |
| Cooling system | | Pressurized radiator | | |
| Radiator fan | | Radial air flow | | |
| Capacities | | | | |
| Fuel tank | gal (ℓ) | 8.1 (31) | | |
| Cooling system | qts. (ℓ) | 4.7 (4.5) | | 5.5 (5.2) |
| Engine oil | qts. (ℓ) | 3.2 (3.0) | 4.3 (4.1) | |
| Transmission case | gal (ℓ) | 4.0 (15) | | |
| Drive train | | | | |
| Clutch | | N/A | | |
| Transmission | | HST (3 range) | | |
| Differential lock | | Standard | | |
| Final drive | | Spur gear | | |
| Brake | | Multi-plate wet disc | | |
| PTO | | Independent | | |
| Rear | rpm | 540 rpm at 2768 engine rpm | 540 rpm at 2592 engine rpm | |
| Mid | rpm | 2500 rpm at 2753 engine rpm | 2500 rpm at 2600 engine rpm | |
| Hydraulics | | | | |
| Type | | Open center | | |
| Pump | | Dual pump | | |
| Total pump output | gpm (ℓ/min.) | 9.8 (37.2) | 9.1 (34.5) | |
| Hydraulic outlet | | Front outlet, Rear outlet | | |
| 3-point hitch | | Category I | | |
| Hydraulic control system | | Position control valve | | |
| Lift capacity | at lift point lbs. (kg) | 2139 (970) | | |
| | 24" behind LP lbs. (kg) | 1676 (760) | | |
| Steering | | Hydrostatic power steering | | |
| Standard tire size | | | | |
| Front | | 7-12 | | |
| Rear | | 12.4-16 | | |
| Traveling speeds (at rated engine rpm) | | | | |
| Forward | mph (km/h) | 0-11.5 (0-18.6) | 0-12.1 (0-19.5) | |
| Reverse | mph (km/h) | 0-9.2 (0-14.8) | 0-9.6 (0-15.5) | |
| Dimensions | | | | |
| Overall length (w/o 3P) | in. (mm) | 99.2 (2520) | | 103.9 (2640) |
| Overall width (min. tread) | in. (mm) | 53.7 (1365) | | |
| Wheelbase | in. (mm) | 65.6 (1666) | | |
| Ground clearance | in. (mm) | 14.6 (370) | | |
| Turning radius with brake | feet (m) | 6.9 (2.1) | | |
| Weight with ROPS | lbs. (kg) | 1786 (810) | 1852 (840) | 2271 (1030) |

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.

B**B2630/B3030****Kubota****SPECIFICATIONS****Implements Specifications****FRONT LOADER**

| Model | | LA403 |
|---|--------------|-----------------------|
| Maximum lift height (to bucket pivot pin) | in. (mm) | 84.6 (2150) |
| Clearance w/ attachment dump | in. (mm) | 67 (1700) |
| Reach at maximum height (ROPS/CAB) | in. (mm) | 24.6 (625)/20.2 (513) |
| Maximum dump angle | degrees | 40 |
| Attachment rollback angle | degrees | 30 |
| Digging depth at bucket leveled | in. (mm) | 5 (127) |
| Overall height in carry position | in. (mm) | 44.7 (1135) |
| Material bucket width | in. (mm) | 54 (1370) / 60(1525) |
| Lift capacity (pivot pin) | lbs. (kg) | 1091 (495) |
| Lift capacity (19.7 in. forward) | lbs. (kg) | 783 (355) |
| Lift capacity (bucket bottom mid point) | lbs. (kg) | 882 (400) |
| Breakout force (19.7 in. forward) | lbf. (N) | 1690 (7517) |
| Breakout force (pivot pin) | lbf. (N) | 2313 (10290) |
| Raising time to full height w/o load | sec. | 3.1 |
| Lowering time w/o load (powerdown) | sec. | 3.7 |
| Attachment rollback time | sec. | 2.3 |
| Attachment dumping time | sec. | 1.6 |
| Rated flow | GPM (ℓ/min.) | 5.2 (19.7) |
| Rated pressure | psi | 2405 (169) |
| Boom cylinder size (Bore × Stroke) | in. (mm) | 1.57×17.6 (40×448) |
| Bucket cylinder size (Bore × Stroke) | in. (mm) | 1.57×19.3 (40×490) |
| Bucket roll breakout force at ground line | lbf. (N) | 2287 (10174) |

BACKHOE

| Model | | BH76 |
|--------------------------------------|----------|--------------|
| Transport height | in.(mm) | 80.4 (2042) |
| Stabilizer spread transport | in.(mm) | 51.8 (1315) |
| Ground clearance | in.(mm) | 12.9 (327) |
| Overall width | in. (mm) | 54.9 (1394) |
| Maximum digging depth | in. (mm) | 92.2 (2341) |
| Digging depth, 2ft. flat bottom | in. (mm) | 91.0 (2311) |
| Digging depth, 8ft. flat bottom | in. (mm) | 69.3 (1761) |
| Operating height, fully raised | in. (mm) | 120.1 (3050) |
| Loading height | in. (mm) | 64.4 (1636) |
| Loading reach | in. (mm) | 48.9 (1242) |
| Reach from swing pivot | in. (mm) | 120.5 (3060) |
| Swing pivot to rear axle center line | in. (mm) | 38.4 (976) |
| Bucket rotation | deg. | 182 |
| Stabilizer spread operating | in. (mm) | 67.6 (1717) |
| Angle of departure per SAE J 1234 | deg. | 18 |
| Leveling angle | deg. | 10.2 |
| Swing arc | deg. | 180 |

MID-MOUNT MOWER

| Model | | RCK60-30B | RC72-30B |
|------------------------------|----------|------------------------|------------|
| Type | | Side discharge | |
| Number of blades | | 3 | 3 |
| Blade length | in.(mm) | 20.6 (523) | 24.6 (625) |
| Mounting method | | Floating | |
| Cutting width | in. (mm) | 60 (1524) | 72 (1826) |
| Cutting height | in. (mm) | 1.5 to 4.0 (38 to 102) | |
| Adjustment of cutting height | | Gauge wheel | |
| Weight (approx.) | lbs.(kg) | 374 (170) | 463 (210) |