

B

B3200HSD

OTHERS



Mid Mount Mower

- Available in both a 60" or 72" mowing deck.
- Full floating type mower deck
- Quick mount mechanism allows mower deck to be mounted and dismantled easily without tools.
- Durable gear box drives blade spindles via E-Type multi-belt utilizing a spring loaded idler pulley.
- Blade spindle grease zerks accessible without removing mower deck shields.
- Cutting height can easily be adjusted from 1.5" to 4.0" in ½" increments by adjusting gauge wheel settings.



Front Mounted Snowblowers

- Available in both 51" or 63"
- Front implement system utilizes a single quick hitch and subframe 2-stage snowblower
- Mid PTO drive system
- Replaceable reversible cutting edge
- Optional manual or hydraulic chute rotation kits available
- Optional hydraulic chute deflector and electric selector valve kit or electric chute deflector
- Optional width extensions (Increases cutting width by 5")



Rotary Broom

- Front implement system which utilizes a single quick hitch and subframe 56.5" maximum sweeping width
- Hydraulic angling
- Adjustable suspension
- Mid PTO drive system
- Parking stands
- Optional side caster wheels for detaching
- Optional rubber dust deflector



Front Mounted Blades

- Available in both 60" or 72"
- Front implement system which utilizes a single quick hitch and subframe
- Front Blade is a heavy duty blade designed for commercial use.
- Hydraulic power angle is a standard feature on the 60" Front Blade.
- HD double bevel cutting edge
- HD replaceable skid shoes
- Hydraulic angling
- Optional rubber cutting edge



Rotary Tillers

- Available in both a 40" and 50" tilling width
- CAT. 1, 3-Point hitch
- Center and offset mounting
- Built in slip clutch for system protection
- Spring loaded rear shield for smooth ground cover
- Gear box and frame are one unit assembly for greater durability

B

B3200HSD

Kubota

OTHERS



Ballast Box

- Mounted on the three point hitch with sand or gravel to counter balance the tractor when operating with a front implement.
- Holds a maximum of 400 lbs. (182 kg) of dry sand.
- The total weight of the ballast box with sand is 500 lbs. (227 kg).
- The proper amount of ballast in loader applications on the B3200 is a maximum of 500 pounds (227 Kg) ballast attached to the 3 point hitch
- The Ballast box is required for loader applications.



Rear 3 Point Snowblower

- The 2-stage snowblower is available in both 51" or 64"
- 3 Point hitch mount
- Replaceable reversible cutting edge
- Oilbath gearbox
- Optional manual or hydraulic chute rotation kits available
- Optional hydraulic chute deflector and electric selector valve kit or electric chute deflector
- Optional width extensions (Increases cutting width by 5") on 64"

Grass Catcher

- Total collection capacity 9.75 bushels (3 grass bags)
- Impeller 6 blade, 13.5" diameter
- Impeller speed 2160 rpm
- Impeller powered by tractor rear PTO