

B

B3300SU

OTHERS



Snowblowers

- Available in both 51" or 63"
- Front implement system utilizes a heavy duty front quick hitch and subframe
- 2-stage snowblower
- Mid PTO drive system
- Replaceable reversible cutting edge
- Optional manual or hydraulic chute rotation kits available
- Optional hydraulic chute deflector and electric selector valve kit or electric chute deflector
- Optional side extensions (Increases cutting width by 5")



Rotary Broom

- Front implement system which utilizes a heavy duty front quick hitch and subframe
- 56.5" maximum sweeping width
- Hydraulic angling
- Adjustable suspension
- Mid PTO drive system
- Parking stands
- Optional side caster wheels for detaching
- Optional rubber dust deflector



Blades

- Available in both 60" or 72"
- Front implement system which utilizes a heavy duty front quick hitch and subframe
- Front Blade is a heavy duty blade designed for commercial use.
- Hydraulic power angle is a standard feature on the 60" or 72" Front Blade.
- HD double bevel cutting edge
- HD replaceable skid shoes
- Hydraulic angling
- Optional rubber cutting edge



Rotary Tillers

- Available in both a 40" and 50" tilling width
- CAT. 1, 3-Point hitch
- Center and offset mounting
- Built in slip clutch for system protection
- Spring loaded rear shield for smooth ground cover
- Gear box and frame are one unit assembly for greater durability



Ballast Box

- Mounted on the three point hitch with sand or gravel to counter balance the tractor when operating with a front implement.
- Holds a maximum of 400 lbs. (182 kg) of dry sand.
- The total weight of the ballast box with sand is 500 lbs. (227 kg).
- The proper amount of ballast in loader applications on the B3200 is a maximum of 500 pounds (227 Kg) ballast attached to the 3 point hitch
- The Ballast box is required for loader applications.

