

# L

## Grand L40 Series

### OTHERS



#### Ballast Box

- Mounted on the three point hitch with sand or gravel to counter balance the tractor when operating with a front implement.
- Holds a maximum of 845 lbs. of dry sand.
- The total weight of the ballast box with sand is 1,000 lbs.
- The Ballast box is required for loader applications.



#### Rotary Tillers

- Available in 60"
- Built-in slip clutch for system protection
- Spring loaded rear shield for smoother ground cover.
- Gear box and frame are a one unit assembly for greater durability
- CAT. 1, 3-point Hitch



#### Rear Mounted Snowblower

- Available in 64" and 74" Cutting Width 2-stage snowblower
- Replaceable Reversible Cutting Edge
- Optional Manual or Hydraulic Chute Rotation Kits Available
- Optional Hydraulic Chute Deflector or Electric Chute Deflector
- Optional Width Extensions (Increases cutting width by 5")



#### Front Mounted Snowblower

- Available in both 62" and 72"
- Front implement system utilizes a single quick hitch and subframe
- 2-stage snowblower
- Mid PTO drive system
- Standard hydraulic chute rotation
- Optional hydraulic chute deflector and electric selector valve kit or electric chute deflector
- Optional width extensions (Increases cutting width by 5")
- Requires Mid PTO
- Includes Blower and Chute Rotator
- Replaceable reversible cutting edge



#### Front Mounted Rotary Sweeper

- Available in both 60" and 72"
- Front implement system which utilizes a single quick hitch and subframe
- Hydraulic angling
- Adjustable suspension
- Mid PTO drive system
- Parking stands
- Optional side caster wheels for detaching
- Optional rubber dust deflector
- Requires Mid PTO

# L

## Grand L40 Series

### OTHERS



#### Front Mounted Blade

- Available in both 72" or 84"
- Front implement system which utilizes a single quick hitch and subframe.
- Front Blade is a heavy duty blade designed for commercial use.
- Hydraulic power angle
- HD double bevel cutting edge
- HD replaceable skid shoes
- Optional rubber cutting on 72" blade
- Spring trip with lockout



#### Mid Mount Mower

- Available on L3240, L3540 and L3940 Only
- Uses tractor mid-PTO (mid-PTO required)
- Floating Deck
  - Right Hand discharge
- 3-Blade Finishing Mower
- 1.5" to 4.5" cutting height
- Mower has four adjustable anti-scalp rollers (one in front center and three in rear) and two front gauge wheels.
- Parallel linkage design for easy mounting.