



L45 Loader/ Landscaper Tractor (TLB)

Competitive Comparison

Model		Kubota L45	JCB Midi CX	John Deere 110	Terramite T9	Yanmar CBL40
Engine	Engine gross power (SAE)	HP 45	50	43	INA	35.4
	Engine net power (SAE)	HP 42.5	48.5	41	33	INA
	PTO	Standard	Option	Standard	--	Optional
	PTO Power	HP 32	25	33	--	24
	Fuel Tank Capacity	gal. 11.9	15.8	15.3	9.5	16.4
Drivetrain	Transmission Type	HST	HST	HST	HST	HST
	Number of Ranges	3	1	3	1	2
	4 Wheel Drive	Standard	Standard	Standard	Option	Standard
	Max Travel Speed	mph 14.9	17.4	16.1	INA	13.7
	Brake	Multi Wet Disk	Multi Wet Disk	Wet Disk	INA	Multi Wet Disk
Hydraulic System	Total hydraulic pump capacity	gal./min. 25	19.0	23.6	10	22
	3-Point Hitch lift capacity @ 24" behind lift point	lbs. 2,756	2,500	2,500	NA	2,540
	Position Control	Standard	Standard	Standard	NA	Optional
	Power Steering	Hydrostatic	Hydrostatic	Hydrostatic	Hydrastatic	Hydraulic
Features	ROPS/FOPS Canopy	Standard	Standard	Standard	INA	Standard
	Backup Alarm	Standard	Standard	Standard	INA	Standard
	Rear Axle Differential Lock	Standard	Standard	Standard	INA	Standard
	Backhoe Crawling Mode	Standard	NA	Standard	NA	NA
	Turn In Place Seat	Standard	Standard	Roll Over	INA	Standard
	Tilt Steering Wheel	Standard	--	NA	INA	INA
	Retractable Seat Belt	Standard	Standard	Standard	INA	Standard
	Spark Arrestor Muffler	Standard	--	Option	INA	INA
Dimensions	Wheelbase	in. 72.5	73	71.5	61	69
	Turning radius with brake	ft. 9.5	11.8	10.3	INA	9.8
	Min. Ground Clearance	in. 12.3	INA	INA	INA	13
	Transport Length	in. 233.7	241.7	259.8	180	234
	Transport Height	in. 106.3	100.4	107.3	82	103
	Overall width	in. 72.5	73	72	60	70
	Weight with loader, backhoe and ROPS/FOPS	lbs. 7,173	8,421	7,600	4,960	7,750
Loader	Loader Quick Coupler	Standard	Standard	Standard	NA	Standard
	Loader Bucket Capacity	cu. ft. 15.5	2.42	--	13.5	13.5
	Auxiliary Hydraulic Flow	gal./min. 11.8	Standard	Available	Option	11
	Bucket Breakout force	lbs. 4,530	5,830	3,965	6,100	4,850
	Dump Clearance Full Height	ft. in. 7' 6"	6' 9"	--	--	7' 3"
	Lift capacity	lbs. 2,848	3,478	2,042	2,300	2,866
	Protected Hoses	Standard	Standard	Standard	NA	NA
	Auto-Leveling System	Hydraulic	Mechanical Spill Guard	Mechanical Spill Guard	NA	Mechanical Spill Guard
Standard bucket width	in. 72	72	72	INA	70	
Backhoe	Backhoe Mounting Method	Quick Mount	Quick Mount	Quick Mount	Permanent	Quick Mount
	Maximum Digging Depth	in. 121	120	121	120	120
	Max. digging force using bucket cylinder	lbs. 5,825	6,025	5,723	5,200	5,798
	Max. digging force using dipperstick cylinder	lbs. 3,779	4,584	3,764	3,010	3,582
	Reach @ Swing Pivot	in. 161	146	158	--	158
	Auxiliary Hydraulic Flow	gal./min. 11.8	INA	--	NA	INA
	Arch Type Boom	Standard	--	Standard	Standard	Standard
	Bucket QC Option	Available	--	Available	Available	Available
	Thumb Option	Available	--	Available	NA	NA

These comparison of specifications are based upon the most reliable data obtainable by Kubota at the time of publication. Kubota reserves the right to change specifications without notice.

Information in this section has been obtained both from literature published by competitors and from other sources available at the time this material was being prepared.

It is correct to the best of our knowledge but due to technological developments it is subject to change without notice.