

Disc Harrows



DH10 Series

	DH1048
Hitch	Cat. 1 (Fits Land Pride Quick Hitch)
Cutting Width	48"
Height	33 3/4"
Length	47"
Weight	421 lbs.
Weight load on each Disc	35 lbs.
No. of disc blades	12
Disc Blade size	16" or 18" Diameter notched or smooth
Disc Blade spacing	7 1/2"
Bearing Hanger	3/8" plate
Bearing Type, 2 per gang	Self aligning, Sealed Bearing
Disc Angle	Front & rear gang: 0, 7, 14, & 21 degrees
Frame Tubes	2" square
Gang Tube	3" x 1 1/2"
Gang Axle	1" square high carbon steel
Disc Scrapers	Not Available
9" Center Sweep	Not Available

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Disc Harrows

DH10 Series

Features	Benefits
Working widths	48", 60"
Cat. 1 3-point hitch	Fits Land Pride Quick-Hitch for easy one-person attachment and removal.
Weight	48" - 412 lbs.; 60" - 533 lbs. Heavy construction helps penetrate ground.
2" Square frame tube	Frame tubing is stronger than angle iron.
Adjustable gang angles	Cutting aggressiveness can be adjusted on the front and rear up to 21 degrees.
3" x 1 1/2" Gang tube, 1" Sq. gang axles, high carbon steel	High carbon square axles offer great strength in punishing conditions.
16" or 18" Notched or smooth disc blades	Choose notched blades for more aggressive digging and cutting action, or the smooth blades for light tilling. (16" blades only on 48" width)
3/8" Thick bearing hangers	Heavy-duty hangers resist the high torque from U-bolts and/or keep the discs out of the ground.
3/8" Frame side plates	Offer additional strength and reinforcement to the gang tube.
Self aligning sealed bearings	Self-aligning bearings offer long life while pounding through hard ground.

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.