

Post Hole Diggers



PD10 Series	
	PD10
Tractor HP	30 HP
Flighting Thickness	1/4"
Auger Dia.	6", 9", and 12" Cast fishtail tip, hardened reversible cutting teeth
Hitch Cat.	I
Boom Tube	2 7/8" O.D.
Yoke Tube	2 7/8" O.D.
Driveline Cat.	II
Gearbox	540 RPM 3:1 Ratio, Operating RPM: 300
Weight	120 lbs (without Auger).

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Post Hole Diggers, PTO

PD10 Series

Features	Benefits
Shorter yoke and boom tubing	Allows post hole digger to be used on sub compact utility tractors (i.e. BX Kubota).
Auger length	30" Auger.
Auger flighting	1/4" Flighting, Semi-double flight.
Cast steel auger fishtail tips	Fishtail tip is an excellent pilot point to get hole started.
Gearbox	15 to 30 HP Horsepower (2" output shaft).
Gearbox warranty	5 Years.
2 7/8" Yoke tubing	Same as our 15 Series Post Hole Digger.
Down pressure kit (optional)	Allows additional down force to be supplied to beam to help force digger into the ground.
Alignment handle (optional)	Helps guide the auger from the tractor seat.
Post Hole Digger stand (optional)	Bracket mounted to bottom of gearbox can incorporate a post hole digger stand. This allows operator to hook up and unhook from tractor more safely. Stand supports unit and will store unit when it is not on the tractor.

I

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.