

Rotary Tillers, Reverse Tine Rotation



RTR15 Series		
Model	RTR1550	RTR1558
Width	50"	58"
Overall Width	56 1/4"	64 1/4"
Weight	455	489
Number of Flanges	6	7
Number of Tines per Flange	4	4
Driveline	Category III Heavy Duty Shear bolt - standard Slip Clutch - optional	
Gearbox	35 HP input at 540 rpm 1.92:1 ratio Cast iron housing, straight bevel gears	
Gearbox Lubrication	SAE 80-90W EP oil	
Drive Chain	#80 roller chain in flowable grease bath	
Drive Chain Lubrication	Shell Alvania EP 00 or equivalent	
Sprockets	Case hardened teeth, splined bores	
Rotor Swing Diameter	15"	
Rotor Shaft Speed	211 rpm at 540 rpm PTO	

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Rotary Tillers, Reverse Tine Rotation

RTR15 Series

Features		Benefits		
Working widths		50", 58" To meet specific customers needs.		
Tractor HP Range		17 - 35 HP		
Gearbox Warranty		3 Years on housings, seals, bearings. Shows our confidence in the product.		
Reverse tilling action		Reverse action 'sucks' tiller into ground, does not walk on top of hard ground like forward rotation tillers can.		
Front deflector		Front deflector is flexible to take the beating from rocks or debris.		
Formed and reinforced rear deflector		Forming gives deflector additional strength. Adjustable deflector allows for various finish results.		
Adjustable skid shoes		Control depth with various settings.		
Solid rotor shaft		1 3/4" Solid steel shaft for strength.		
Double lip seal on rotor bearing		Double lip seal helps keep the dirt out and the grease in.		
4 'C' Shaped heat-treated tines per flange		'C' Shaped tines require less HP to move through the ground.		
15" Rotor swing diameter		For deep tilling and turning the soil over faster.		
6 1/2" Digging depth		For deep soil penetration.		
Cat. 3 Driveline		Cat. 3 Driveline with heavy-duty shear-bolt or slip-clutch		
Fully shielded shear pin or slip-clutch driveline		Protects the gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.		
Stamped chain cover		Stamped forming gives the chain cover strength.		
#80 Drive chain enclosed in oil bath		Heavy drive chain stretches less, and oil bath keeps wear to a minimum.		
Adjustable parking stand		Allows for easy hook-up and storage.		
Plate steel upper hitch		Plate steel is stronger than flat bar type hitch.		
Clevis lower hitch		Provides additional strength and easy one person hook-up.		
Hitch sideshift capabilities		Sideshift tiller to cover right tire track. Gearbox slides with tiller.		
Sideshift dimensions	50" width	25"-25" Std.	12"-38" Max. right	31"-19" Max. left
	58" width	29"-29" Std.	12"-46" Max. right	35"-23" Max. left
Fits Land Pride Quick-Hitch		Allows for quick & easy one person hook-up. Offset cannot be used with Quick-Hitch.		

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.