

Landscape Rakes



LR05 and LR15 Series

	LR0548	LR0560	LR1560
Rake Width	48"	60"	60"
Approximate Weight 6(lbs.)	98	113	241
Horsepower Rating	15-20		20-35
Rake Height	12"		16 1/2"
Teeth Size	1/4" x 3/4" wide		5/16" x 1" wide
Hitch Type	Cat. 0 With Cat. 1 pins		Cat. 1 Fits Land Pride Quick Hitch
Angle and Position	5 Forward Up to 30 degrees Right or left		5 Forward Up to 30 degrees Right or Left 7 Reverse Up to 45 degrees Right or Left
Teeth Spacing	1 3/4" Centers		2" Centers
Teeth Material	High Carbon Spring Steel		
Gauge Wheel Option*	Dual Solid Wheels 2 3/4" x 8 1/4"		Dual Narrow Width Wheels 13" X 4" Dual Wide Width Wheels 13" X 6 1/2"
Grader Blade Option	Flip Down Self Supporting Grader Blade with Blade-up Locking Pins		Flip Down Self Supporting Grader Blade with Blade-up Locking Handles and locking pins

* Dual gauge wheels are capable of supporting the optional grader blades.

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Landscape Rakes

LR05 Series

Features	Benefits
Cat. 0 with Cat. 1 pins on 05 Series	Fits smaller tractors with Cat. 0 hitch.
Retractable Parking Stand	Keeps the frame off the ground and makes hook-up easier.
Various working widths	(48" & 60") Allows adaptability to many tractor sizes.
5 Forward angles	Vary how much material to move.
High carbon spring steel teeth	Teeth have "memory" to spring back to shape.
Individual Replaceable teeth	Replace a damaged tooth without removing all of the teeth.
Optional Dual Gauge Wheels	Ease of depth control and provides attachments for a grader blade.
Optional Grader Blade	Adding a flip down grader blade with end plates allows one to move and level dirt as well as other materials.
Moldboard Blade adaptable	Moldboard Blade assembly can easily replace the rake assembly for more versatility to ones implement.

LR15 Series

Features	Benefits
3 1/2" Pivot tube	Heavy frame tube. Heaviest in its class.
Rake teeth support channel	Design with channel support. This design supports the rake teeth better than competitor models. Eliminates premature bending and teeth breakage.
Quick-Hitch adaptable	Fits Land Pride Quick-Hitch for easy one-person attachment.
Retractable Parking Stand	Keeps the frame off the ground and makes hook-up easier.
Dual gauge wheels	Gives operator precise depth control. Wide & Narrow wheels available.
Flip down grader blade	Option lets you use your rake as a light-grading tool.
Rear Blade option	Same frame can be used with RB15 Series Rear Blade. Increased versatility.
Replaceable teeth	Teeth can easily be replaced individually.
Angle 7 forward positions and 5 reverse positions	Versatility in operation. Vary how much material to move.
Working widths	60", 72", 84", 96" to meet a wide range of customer needs.
Tractor HP Range	20-35 HP
High carbon spring steel	Allows teeth to keep their shape.
Warranty	One year parts & labor.

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.