

**Rotary Tillers, Reverse Tine Rotation**



<b>RTR10 Series</b>	
	<b>RTR1042</b>
<b>Width</b>	42"
<b>Overall Width</b>	47 5/16"
<b>Weight</b>	403
<b>Number of flanges</b>	5
<b>Number of Tines per Flange</b>	4
<b>Driveline</b>	Category II Shear bolt - standard Slip Clutch - optional
<b>Gearbox</b>	25 HP input at 540rpm 1.92:1 ratio Cast iron housing, straight bevel gears
<b>Gearbox Lubrication</b>	SAE 90 oil
<b>Drive Chain</b>	#80 roller chain in flowable grease bath
<b>Drive Chain Lubrication</b>	Shell Alvania EP 00 or equivalent
<b>Sprockets</b>	Case hardened teeth, splined bores
<b>Rotor Swing Diameter</b>	15"
<b>Rotor Shaft Speed</b>	225 rpm at 540 rpm PTO
<b>Recommended Maximum PTO HP</b>	25 HP
<b>Hitch Type</b>	Category I, offsetable, works with Land Pride Quick-Hitch (Note: Cannot be offset when using the Quick-Hitch)

*Designs, specifications, features and information are subject to change without notice.*

*This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.*

**Rotary Tillers, Reverse Tine Rotation**

**RTR10 Series**

Features		Benefits		
American made		Many tillers are imported. American made means better parts availability.		
Gearbox Warranty		3 Years on housing, seals, & bearings. shows our confidence in the product.		
Working widths		42", 50", 58" to meet specific customer needs.		
Tractor HP range		17-25 HP		
Reverse tilling action		Reverse action 'sucks' tiller into ground, does not walk on top of hard ground like forward rotation tillers can.		
Front deflector		Front deflector is flexible to take the beating from rocks or debris.		
Formed and reinforced rear deflector		Keeps dirt in and leaves a level finish. Forming gives deflector additional strength. Adjustable deflector allows for various finish results.		
Adjustable skid shoes		Control depth with seven adjustments.		
Solid rotor shaft		1 3/4" Solid steel rotor shaft for strength.		
Double lip seal on rotor bearing		Double lip seal helps keep the dirt out and the grease in.		
4 'C' shaped heat-treated tines per flange		'C' Shaped tines require less HP to move through the ground.		
15" Rotor swing diameter		For deep tilling and turning the soil over faster.		
6 1/2" Digging depth		For deep soil penetration.		
Fully shielded shear pin or slip-clutch driveline		Protects the gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins.		
Stamped chain cover		Stamped forming gives the chain cover strength.		
#80 Drive chain enclosed in oil bath		Heavy drive chain stretches less, and oil bath keeps wear to a minimum.		
Adjustable parking stand		Allows for easy hook-up and storage.		
Plate steel upper hitch		Plate steel is stronger than flat bar type hitch.		
Clevis lower hitch		Provides additional strength and easy one person hook-up.		
Adjustable lower hitch		Offset unit to cover right tire track.		
Offset Dimensions	42" width	16"-26" std.	13"-29" Maximum Right	23"-19" Maximum Left
	50" width	25"-25" std.	18"-32" Maximum Right	32"-18" Maximum Left
	58" width	29"-29" std.	22"-36" Maximum Right	36"-22" Maximum Left
Fits Land Pride Quick-Hitch		Allows for quick and easy one person hook-up. (Offset cannot be used with Quick-Hitch.)		

*Designs, specifications, features and information are subject to change without notice.*

*This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.*