

Disc Harrows



	DH1048	DH1060	DH1560	DH1572
Hitch	Cat. 1 (Fits Land Pride Quick Hitch)			
Cutting Width	48"	60"	60"	72"
Height	33 3/4"	34 3/4"	40"	
Length	47"	48"	56"	56 1/2"
Weight	421 lbs.	533 lbs.	628 lbs.	714 lbs.
Weight load on each Disc	35 lbs.	33 lbs.	38 lbs.	34 lbs.
No. of disc blades	12	16	16	20
Disc Blade size	16" or 18" Diameter notched or smooth		18" Diameter notched or smooth	
Disc Blade spacing	7 1/2"			
Bearing Hanger	3/8" plate		3/8" plate, 2 each 5/8" U-bolts	
Bearing Type, 2 per gang	Self aligning, Sealed Bearing			
Disc Angle	Front & rear gang: 0, 7, 14, & 21 degrees			
Frame Tubes	2" square		2 1/2" square	
Gang Tube	3" x 1 1/2"		3" x 2"	
Gang Axle	1" square high carbon steel			
Disc Scrapers	Not Available		Optional, Adjustable	
9" Center Sweep	Not Available		Optional, Removes Center Ridge	

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Disc Harrows

DH10 Series

Features	Benefits
Working widths	48", 60"
Cat. 1 3-point hitch	Fits Land Pride Quick-Hitch for easy one-person attachment and removal.
Weight	48" - 412 lbs.; 60" - 533 lbs. Heavy construction helps penetrate ground.
2" Square frame tube	Frame tubing is stronger than angle iron.
Adjustable gang angles	Cutting aggressiveness can be adjusted on the front and rear up to 21 degrees.
3" x 1 1/2" Gang tube, 1" Sq. gang axles, high carbon steel	High carbon square axles offer great strength in punishing conditions.
16" or 18" Notched or smooth disc blades	Choose notched blades for more aggressive digging and cutting action, or the smooth blades for light tilling. (16" blades only on 48" width)
3/8" Thick bearing hangers	Heavy-duty hangers resist the high torque from U-bolts and/or keep the discs out of the ground.
3/8" Frame side plates	Offer additional strength and reinforcement to the gang tube.
Self aligning sealed bearings	Self-aligning bearings offer long life while pounding through hard ground.

DH15 Series

Features	Benefits
Working widths	60", 72"
3-point Hitch	Cat. 1 (Fits Land Pride Quick-Hitch for easy one-person attachment and removal.)
Weight	60" - 629 lbs.; 72" - 714lbs. Heavy construction helps penetrate ground.
2 1/2" Square frame tube	Frame tubing is stronger than angle iron.
Adjustable gang angles	Cutting aggressiveness can be adjusted on the front and rear up to 21 degrees.
Adjustable gang handles	Gives the user something to hold on to while adjusting gang angles.
3" x 2" Gang tube, 1" Square gang axles, high carbon steel	High carbon square axles offer great strength in punishing conditions.
18" Notched or smooth disc blades	Choose notched blades for more aggressive digging and cutting action, or the smooth blades for light tilling.
3/8" Thick bearing hangers with two 5/8" U-bolts	Heavy-duty hangers resist the high torque from U-bolts and/or keep the discs out of the ground.
1/2" Frame side plates	Offer additional strength and reinforcement to the gang tube.

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.