

Rear Blades



| RB25 & RB35 Series | | | | |
|---------------------------|--|--------|--|--------|
| | RB2572 | RB2584 | RB3572 | RB3584 |
| Blade Width | 72" | 84" | 72" | 84" |
| Approximate Weight (lbs.) | 369 | 396 | 484 | 533 |
| Horsepower Rating | 25-60 | | 35-80 | |
| Hitch Type | Cat. 1 Fits Land Pride Quick Hitch | | Cat. 1 & 2 Fits Land Pride Quick Hitch | |
| Parking Stand | Retractable | | | |
| Angle/Position | 9 Forward up to 60 degrees right or left 5 Reverse up to 60 degrees right or left | | | |
| Blade Height | 17 1/2" | | | |
| Blade Thickness | 5/16" | | | |
| Cutting Edge | 1/2" x 6" Heat treated Replaceable & Reversible (Double bevel) | | | |
| Offset | No | | 40 degrees swing, 12" right & 12" left | |
| Tilt | Limited to tractor's lower 3-point arm adjustment | | 5 Positions up to 30 degrees right or left | |
| Options | Single Gauge Wheel, Skid Shoes End Plates Hydraulic Cylinder (Accessory for Single Gauge Wheel & RB35 Frame Offset) Landscape Rake Adaptable | | | |

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Rear Blades

RB25 Series

| Features | Benefits |
|--|--|
| Working widths | 72", 84", 96" |
| HP range | 25-60 HP |
| Fits Land Pride Quick-Hitch | Allows for quick and easy one person hook-up. |
| Retractable Parking Stand | Keeps the frame off the ground and makes hook-up easier. |
| 5/16" Moldboard thickness | Offers thickness for rugged work. |
| 17 1/2" Moldboard height | Rolls the material for less drag. |
| 1/2 1/2" x 6" Heat-treated reversible cutting edge | Gives twice the life from the cutting edge by being able to reverse it. |
| 9 Forward and 5 Reverse positions | Many angles for diverse jobs and results. |
| Skid shoes (optional) | Set depth of blade to clear obstructions like manhole covers, street cracks. |
| Side plates (optional) | Side plates allow blade to hold in material to move. |
| Gauge wheel (optional) | Set depth of blade to do level grading. |
| Landscape Rake adaptable | Remove moldboard and add rake element to add diversity of frame. |
| Warranty | One year parts & labor. |

RB35 Series

| Features | Benefits |
|--|---|
| Working widths | 72", 84", 96" |
| HP rating | 35-80 HP |
| Cat. 1 & 2 Hitch | Fits wide variety of tractors. |
| Fits Land Pride Quick-Hitch | Allows for quick and easy one person hook-up. |
| Retractable Parking Stand | Keeps frame off ground during storage, also allows for easy hook-up. |
| 5/16" Moldboard thickness | Offers thickness for rugged work. |
| 2" x 2 x 3/8" Angle iron reinforcement on 84" & 96" Moldboards | Gives 84" & 96" moldboard added strength. |
| 17 1/2" Rolled moldboard | Rolls material for less drag. |
| 1/2 1/2" x 6" Heat-treated reversible cutting edge | Gives twice the life from the cutting edge by being able to reverse it. |
| Heavy turntable housing (dog house) | Keeps all parts fitting snug to eliminate premature wear. Extends life on threaded shaft. |
| 9 Forward and 5 reverse positions | Many angles for diverse jobs and results. |
| 5 Tilt position | 5 Different positions for blade tilt. |
| 12" Offset | Blade can be offset 12". Helps extend blade past tractor tire. |
| Gauge wheel (optional) | Can be used for more precise grading by keeping the moldboard at a fixed position. |

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.