

Soil Pulverizers



SP2060, SP2072, SP3072 & SP3084

	SP2060	SP2072	SP3072	SP3084
Width	60"	72"	72"	84"
Weight (With Single Roller- lbs.)	491	561	671	721
Max Engine Hp.	35 Hp.	35 Hp.	50 Hp.	50 Hp
Number Of Shanks	21	25	25	29
Number Of Spikes - Single Roller	86	103	103	116
Number Of Spikes - Double Roller	N/A	N/A	206	232
Height	36 1/2"		36 1/2"	
Front To Back Length Single Roller	24"		27 1/4"	
Front To Back Length Double Roller	N/A		35 1/4"	
Shank Spacing	2 13/16"		2 13/16"	
Spiked Roller Tube Diameter	5 9/16" O.D		6 5/8" O.D. (Optional Second Roller 5 9/16")	
H-Beam	10"		12"	
A-Frame	1/2" x 2 1/2" Flat Bar		3/8" Plate	
Springs-Front Roller	32 lbs./inch		32 lbs./inch	
Springs - Rear Roller	N/A	N/A	15 lbs./inch	
Spike Material	3/8" x 1 1/4" Steel, Replaceable Heat Treated Sleeves		3/8" x 1 1/4" Steel, Replaceable Heat Treated Sleeves	
Hitch	Cat. 1		Cat. 1	

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Soil Pulverizers

SP20 & SP30 Series

Features	Benefits
Working widths	20 Series: 60", 72"; 30 Series: 72", 84"
HP Range	20 Series: 20-35 HP; 30 Series: 30-50 HP
Replaceable heat-treated sleeves	Heat-treated replaceable sleeves on roller protect spike. Easily replace the sleeve when worn vs. replacing entire spike.
3/8" Steel spikes welded to the roller's surface	Spikes are welded to the roller's surface rather than to a hole. Damaged spikes can be cut off and replaced.
Self-aligning bearings with double lip seals on rear roller	Self-aligning bearings conform to the roller and shafts.
1" Diameter shaft in roller	Heavy shaft can handle the shock loads from the roller.
Roller has high number of steel spikes	Better pulverization, more spikes than most competitors
H Beam	20 Series: H Beam-10"; 30 Series: H Beam-12"
10 1/2" x 2" x 2 1/2" Scarifier teeth	Scarifier teeth are heat-treated for long life and can be reversed when one side wears down.
Warranty	One year parts and labor
Fits Land Pride Quick-Hitch	Cat. 1 3-point fits Land Pride Quick-Hitch for easy on-off with one person.

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.