

**Rotary Tillers, Standard Tine Rotation**



| RTA15 Series               |  |         |
|----------------------------|--|---------|
|                            | RTA1550  | RTA1558 |
| Width                      | 50"  | 58"     |
| Overall Width              | 56 1/4"  | 64 1/4" |
| Weight                     | 412  | 444     |
| Number of Flanges          | 6  | 7       |
| Number of Tines per Flange | 4  |         |
| Driveline                  | Category III Heavy Duty<br>Shear bolt - standard<br>Friction Clutch - optional   |         |
| Gearbox                    | 35 HP input at 540 rpm 1.92:1 ratio<br>Cast iron housing, straight bevel gears   |         |
| Gearbox Lubrication        | Gear Lube 80-90W EP  |         |
| Drive Chain                | #80 roller chain in flowable grease bath   |         |
| Drive Chain Lubrication    | Shell Alvania EP 00 or equivalent  |         |
| Sprockets                  | Case hardened teeth, splined bores   |         |
| Rotor Swing Diameter       | 15"  |         |
| Rotor Shaft Speed          | 211 rpm at 540 rpm PTO   |         |
| Recommended Maximum PTO HP | 35 HP  |         |
| Hitch Type                 | Category I, Sideshift capabilities, works with Land Pride Quick-Hitch<br>(Note: Sideshift capabilities also works with Land Pride Quick-Hitch) |         |

*Designs, specifications, features and information are subject to change without notice.*

*This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.*

**Rotary Tillers, Standard Tine Rotation**

**RTA15 Series**

| Features  | Benefits  |
|---|---|
| Working widths                                    | 50", 58" to meet specific customer needs.   |
| Tractor HP range                                  | 17 - 35 HP  |
| Gearbox warranty                                  | 3 Year on housing, gears, seals and bearings. Shows our confidence in the product.                              |
| Fits Land Pride Quick-Hitch                       | Allows for quick and easy one person hook-up. Cannot be used with offset.                                       |
| Sideshift capabilities                            | Sideshift tiller to cover right tire track. Gearbox slides with tiller.   |
| Sideshift dimensions 50"                          | 25-25 Std.; 12-38 Max. right; 31-19 Max. left   |
| Sideshift dimensions 58"                          | 29-29 Std.; 12-46 Max. right; 35-12 Max. left   |
| Formed and reinforced rear deflector              | Forming gives deflector additional strength. Adjustable deflector allows for various finish results.            |
| Clevis hitch                                      | Provides additional strength and easy one person hook-up.   |
| Skid Shoes  | Control depth with various settings.  |
| 6 1/2" Digging depth                              | For deep soil penetration.  |
| Adjustable Parking Stand                          | Easy hook-up and storage.   |
| Plate steel hitch                                 | Plate steel is stronger than flat bar type hitch.   |
| 4 'C' Shaped heat-treated tines per flange        | 'C' Shaped tines require less HP to move through the ground.  |
| Solid rotor shaft                                 | 1 3/4" Solid steel shaft for strength.  |
| Cat. 3 Driveline                                  | Cat. 3 Driveline with heavy-duty shear-bolt or slip-clutch  |
| 15" Rotor swing diameter                          | For deep tilling and turning the soil over faster.  |
| Double lip seal on rotor bearing                  | Double lip seal helps keep the dirt out and the grease in.  |
| #80 Drive chain enclosed in oil bath              | Heavy drive chain stretches less, and oil bath keeps wear to a minimum.   |
| Stamped chain cover                               | Stamped forming gives the chain cover strength.   |
| Fully shielded shear pin or slip-clutch driveline | Protects the gearbox and rotor shaft upon hitting obstructions. Slip-clutch saves having to replace shear-pins. |

*Designs, specifications, features and information are subject to change without notice.*

*This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.*