

**Rotary Tillers, Standard Tine Rotation**



RTA20 and RTR20 Series				
Model	RTA2064	RTR2064	RTA2072	RTR2072
Weight	689 lbs.	748 lbs.	734 lbs.	795 lbs.
Tilling Width	64"		72"	
Overall Width	70 1/4"		77 5/16"	
Offset Capabilities	14"		18"	
Number of Flanges	8		9	
Number of Tines per Flange	6			
PTO Driveline	ASAE Category III Heavy Duty Friction Clutch or Shear Bolt			
Gearbox	40 HP Input at 540 rpm 1.92:1 Ratio Cast Iron Housing, Straight Bevel Gears			
Gearbox Lubrication	SAE80-90W EP oil			
Drive Chain	#80 roller chain in flowable grease bath			
Drive chain lubricant	Shell Alvania EP 00 or equivalent			
Sprockets	Splined Bores			
Rotor Swing Diameter	17"			
Rotor Shaft Speed	220 rpm at 540 rpm PTO			

*Designs, specifications, features and information are subject to change without notice.*

*This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.*

**Rotary Tillers, Standard Tine Rotation**

**RTA20 & RTR20Series**

Features	Benefits
<b>20 Series</b>	Fills the gap between our 15 and 25 Series Tillers, both in size and price.
<b>Tractor HP</b>	23 - 40 HP.
<b>Gearbox Warranty</b>	3 Years on housing, gears, shafts & seals. Shows our confidence in the product.
<b>Working Widths</b>	64" & 72" Meets a wide range of customer needs.
<b>Formed Deck</b>	Handles material more efficiently, sheds water.
<b>Integral Hitch</b>	Upper hitch, gearbox and gearbox mount brought together to form a stronger overall hitch frame.
<b>Clevis Style Lower Hitch</b>	Allows easier hook-up of lower 3-point arms.
<b>Cat. 1 Hitch fits Land Pride Quick-Hitch</b>	Allows for quick and easy one-person hook-up. Offset is not comparable with Quick-Hitch.
<b>RTR Reverse rotation model or RTA forward rotation model</b>	Land Pride has the market on reverse rotation. This brings in a quality tiller at a more affordable price for landscapers. We offer forward rotation for contractors who want it.
<b>Reverse tilling action</b>	Reverse action 'sucks' tiller into ground, does not walk on top of hard ground like forward rotation tillers can.
<b>Sideshift capability</b>	Sideshifts by loosening 6 U-bolts and sliding hitch points and gearbox over. Allows covering right tire track.
<b>Parking Stand</b>	Allows for easy hook-up and storage
<b>Six tines standard on RTR20 Four tines standard on RTA20 with six being optional</b>	Six tines cut through the ground smoother.
<b>C Tines</b>	C Tines take less horsepower to move through the ground.
<b>17" Rotor swing diameter</b>	For deep tilling action.
<b>Double lip seal on rotor bearing</b>	Double lip seal keeps the dirt out and the grease in.
<b>#80 Drive chain enclosed in oil bath</b>	Heavy-duty drive chain reduces stretching. Oil keeps constant lubrication and holds wear to a minimum.
<b>Easy to adjust chain tightener</b>	Cast iron chain tightener is a simple bolt adjustment to keep constant tension on the chain.
<b>Stamped chain cover</b>	Stamped forming adds additional strength.
<b>Adjustable skid shoes</b>	Control depth from various settings.
<b>Cat. 3 driveline with slip-clutch (option)</b>	Heavy driveline for rough conditions. Slip-clutch protects other drive train components.
<b>Material separator behind tilling action (RTR only)</b>	3/8" Rods sift the material letting bigger items fall first. Sifted soil falls last burying the bigger items. Attachment is one all welded piece for easy assembly.
<b>Formed rear deflector with springs</b>	Formed steel gives the rear deflector additional strength. Springs allow deflector to bounce as it hits obstructions.

*Designs, specifications, features and information are subject to change without notice.*

*This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.*