

Rotary Cutters, Single Deck



RCR2660 and RCR2672 Models		
	RCR2660	RCR2672
Cutting Width	60"	72"
Overall Width	67"	79"
Overall Length (Including Tailwheel)	114"	126"
Blade Tip Speed	12,384 fpm/788 rpm	14,861 fpm/788rpm
Machine Weight (with Chain Guards)	1,002	1,046
Driveline	ASAE Category 4	
Slip Protection	4 Plate Slip Clutch	
Recommended Tractor HP	40-110 maximum	
PTO Speed	540 rpm	
Gearbox	540 rpm PTO Driven Gearbox 1:1.46 Speed-Up Beveled Gears Cast Iron Housing	
Gearbox Lubrication	80-90W EP oil	
Gearbox Output Shaft	2" dia.	
Cutting Height	2" - 12"	
Deck Material Thickness	10 Gauge	
Side Panel Thickness	1/4"	
Deck Height	9 1/8" (Bottom of Deck to Bottom of Skid Shoe)	
Deck Construction	All welded construction	
Skids	Replaceable	
Tailwheel Mount Assembly	Welded arm and Caster Fork	
Tailwheel	4.00 x 8 x 15 Laminated Tire with cast iron hub and tapered roller bearings	
Hitch	Category I or II	
Stump Jumper	Round Pan 3/16" x 25"	Round Pan 3/16" x 32"
Blades (2)	1/2" x 4" x 25" Heat Treated Alloy Steel Free-Swinging High Lift	1/2" x 4" x 29" Heat Treated Alloy Steel Free-Swinging High Lift
Blade Bolt	Keyed with harden flat washer and lock nut	
Blade Cutting Capacity	2"	
Front Guard	Chain Guard - Standard Rubber Guard - Available through Parts Department	
Rear Guard	Chain Guard - Standard	

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

**Rotary Cutters, Single Deck**

**RCR2660 and RCR2672 Models**

Features		Benefits
Cutting Width	60"	72"
Overall Width	67"	79"
Overall Length (Including Tailwheel)	114"	126"
Blade Tip Speed	12,384 fpm/788 rpm	14,861 fpm/788rpm
Machine Weight (with Chain Guards)	1,002#	1,046#
Driveline	ASAE Category 4	
Slip Protection	4 Plate Slip Clutch	
Recommended Tractor HP	40-110 maximum	
PTO Speed	540 rpm	
Gearbox	540 rpm PTO Driven Gearbox 1:1.46 Speed-Up Beveled Gears Cast Iron Housing	
Gearbox Lubrication	80-90W EP oil	
Gearbox Output Shaft	2" dia.	
Cutting Height	2" - 12"	
Deck Material Thickness	10 Gauge	
Side Panel Thickness	1/4"	
Deck Height	9 1/8" (Bottom of Deck to Bottom of Skid Shoe)	
Deck Construction	All welded construction	
Skids	Replaceable	
Tailwheel Mount Assembly	Welded arm and Caster Fork	
Tailwheel	4.00 x 8 x 15 Laminated Tire with cast iron hub and tapered roller bearings	
Hitch	Category I or II	
Stump Jumper	Round Pan 3/16" x 25"	Round Pan 3/16" x 32"
Blades (2)	1/2" x 4" x 25" Heat Treated Alloy Steel Free-Swinging High Lift	1/2" x 4" x 29" Heat Treated Alloy Steel Free-Swinging High Lift
Blade Bolt	Keyed with harden flat washer and lock nut	
Blade Cutting Capacity	2"	
Front Guard	Chain Guard - Standard Rubber Guard - Available through Parts Department	
Rear Guard	Chain Guard - Standard	

*Designs, specifications, features and information are subject to change without notice.*

*This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.*