

Broadcast Spreaders

FSP500, FSP700 & FSP1000 Series			
	FSP500	FSP700	FSP1000
Capacity (Maximum Cu.ft. & pounds)	5.83 cu. ft. (350 lbs.)	9.18 cu. ft. (563 lbs.)	12.18 cu. ft. (673 lbs.)
Overall Dimensions	37" x 40"	44" x 46"	46.8" x 46"
Loading Height	36"	41"	44.5"
Weight	119	128	139
3-Point Attachment	Category 1	Category 1	Category 1
Net Spreadable Width			
Granular	39' - 46'	39' - 46'	39' - 46'
Crystalline	20' - 23'	20' - 23'	20' - 23'
PTO Attachment Type	1 3/8"	1 3/8"	1 3/8"
Transmission Ratio	1:1	1:1	1:1
Min. Tractor HP	15 HP	18 HP	20 HP
Range of Spreading Possibility (lbs/acre)	44 - 890	44 - 890	44 - 890

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Spreaders

FSP500, FSP700 & FSP1000 Series

Features	Benefits
Hopper capacity	FSP500-350 lbs.; FSP700-563 lbs.; FSP1000-673 lbs. to meet specific customer needs.
Spreading capacity	Highly productive at 44 to 890 lbs. per acre.
Spin-type broadcast	For even spreading and productive coverage up to 54 ft.
One piece molded polyethylene hopper	Plastic construction to eliminate corrosion. Seamless for accurate and consistent emptying.
Heavy-duty tubular frame	Supports the weight when full.
Tow hook	Handles up to 1200 pounds.
540 RPM shielded PTO	For added safety.
Shielded Front	Prevents spreading of material in front of the spreader.
Stainless steel distributor vanes	Protects from corrosive material to enhance longevity.
Adjustable distributor vanes	Four adjustable positions to obtain maximum spreading precision and uniformity.
Plastic agitator wheel with steel arm	Standard equipment and is useful when spreading powder type materials that tend to bridge.
Stainless steel orifice doors	Protects from corrosive material enabling doors to operate smoothly.
Plated adjustment levers	Protects from corrosive material to enhance longevity.
Vinyl cover available	Optional vinyl cover with elastic and buckle keeps wind and rain out and material in.
Cat. 1 3-point hitch	For attachment to a wide range of tractors.

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.