

Disc Harrows



DH25 Series

	DH2572
Hitch	Cat. 1 & Cat. 2
Cutting Width	72"
Height	41 1/2"
Length	84 1/2"
Weight	947 lbs.
Weight load on each Disc	59 lbs.
No. of disc blades	20
Disc Blade size	20" or 22" Diameter
Disc Blade spacing	7 1/2"
Bearing Hanger	1/2" plate, 2 each 5/8" u-bolts
Bearing Type, 2 per gang	Self aligning, Sealed Bearing
Disc Angle	Front gang: 0, 7, 14, & 21 degrees with angling adjustment handle Rear Gang: 7, 14 & 21 degrees With angling adjustment handle
Frame Tubes	3" square
Gang Tube	4" X 3"
Gang Axle	1 1/8" square high carbon steel
Disc Scrapers	Optional, Adjustable
9" Center Sweep	Optional, Removes Center Ridge

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Disc Harrows

DH25 Series

Features	Benefits
Working widths	72"
Cat. 1 & 2 3-point hitch	Fits a wide variety of tractors.
Quick-Hitch compatible	Fits Land Prides Quick-Hitch for easy one-person attachment and removal.
Weight	72" = 947 lbs.; 96" = 1143 lbs. Heavy construction helps penetrate ground
3" Square frame tube	Heavy frame can handle 100 HP tractors.
Ball bearings	Self-aligning, sealed ball bearings.
Adjustable gang angles	Vary the degree of aggressiveness on both front and rear gangs.
Gang adjustment handle	Gives the user something to hold on to while adjusting the gang angles.
4" x 3" Gang tube	The gang tube resists twisting due to 4" horizontal width.
1 1/8" Square gang axles	Large axles can resist the high load put on them as the discs roll through the ground.
20" or 22" Notched disc blades	Larger discs will penetrate harder ground.
1/2" Thick bearing hangers	1/2" Thick bearing hangers resist high torque.
Optional scrapers	Scrapers will clean the disc blades off which can plug up and/or keep the discs out of the ground due to mud build-up. Adjustable.

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.