

Rear Blades



RBT40 Series	
	RBT4084
Blade Width	84"
Approximate Weight (lbs.) w/manual links	689
Maximum Engine Horsepower	100 HP - 2 Wheel drive
Maximum G.V.W. (lbs.)	9500
Hitch Type	Cat. 1 & 2 Fits Land Pride Quick Hitch
Moldboard Height	17"
Moldboard Thickness	5/16" reinforced, 1/4" tapered reinforcement channel
MoldBoard Kingpin	3"
Blade Angle	Manual: Hydraulic:
	7 positions in 15 deg. increments (1 center, 3 clockwise & 3 counterclockwise) Up to 45 degrees in either direction.
Angle Cylinder	3 1/2" X 16" X 1 1/4"
Tilt Angle (Manual or Hydraulic)	Up to 15 degrees
Tilt Cylinder	3" X 6" X 1 1/4"
Frame Offset (Manual or Hydraulic)	Up to 30 inches left and right
Offset Cylinder	3 1/2" X 16" X 1 1/4"
Cutting Edge	1/2" x 6" Heat treated reversible blade
Main Frame	Fully enclosed welded, formed box
Parking Stand	Retractable
Options	Skid Shoes End Plates Double Selector Valve and Cushion Valve

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Rear Blades

RBT40 Series

Features	Benefits
HP Rating	65 to 100 HP
3 Way Blade	Tilt, angle and offset features available hydraulically or manually.
Angle	Up to 45 degrees.
Offset	Up to 30" left or right.
Tilt	Tilt to 15 degrees.
17 inch Moldboard	Precisely formed moldboard rolls dirt and debris with ease.
5/16" Moldboard thickness with box reinforcement	Thick material with fully welded box reinforcement creates a strong moldboard to handle tough jobs.
3" Moldboard King pin	Heavy pin for its class of blade.
Working widths	84", 96", 108"
Cat. 1 or 2	Fits wide variety of tractors.
Fits Land Pride Quick-Hitch	Quick and easy attaching without leaving tractor seat.
Fully welded main frame	Fully welded adds overall strength and rigidity to blade frame.
Retractable parking stand	Able to store the unit with the frame off the ground, also aids in attaching to tractor.
Reversible cutting edge	Get twice the wear from the cutting edge by flipping it over.
Warranty	One year parts & labor.
Accessories	
Skid shoes	Skid shoes help protect from hitting low obstructions by keeping the moldboard off the ground.
Cushion valve	Helps protect the moldboard and cylinders in the event an obstruction is hit by allowing hydraulic fluid to bypass the cushion valve and flow back towards the tractor.
Side plates	Side plates hold material in and allows it to be moved.
Cushion valve	Protects from shock loads. Cylinders and mold protection.
Selector Valve	Provides a way to operate 2 cylinders at one outlet, thereby reducing the number of required outlets by one.

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.