

Rotary Cutters, Single Deck



RCR1884 Model	
	RCR1884
Cutting Width	84"
Overall Width	89"
Overall Length with Tail Wheel	133"
Blade Tip Speed	17,113 fpm
Machine Weight (with Front Rubber Guard and Rear Metal Band)	851 lbs. without driveline
Driveline	ASAE Category 4
Driveline Protection	Slip Clutch
Recommended Tractor PTO HP	45 - 90 HP
PTO Speed	540 rpm
Gearbox HP Rating	90 HP
Gearbox	1:1.44 Speed-Up Beveled Gears with Cast Iron Housing
Gearbox Oil Type	80-90W EP oil
Cutting Height	2" - 11"
Deck Material Thickness	10 Ga.
Deck Height (Bottom of Deck to Bottom of Skid Shoe)	9 1/8"
Skid Construction	Standard 1/4" x 2 1/2" welded on
Tailwheel Mount Assembly	Welded arm and Caster Fork
Tailwheel	4" x 8" x 15" Laminated Tire
Hitch	Category I or Category II Quick Hitch
Stump Jumper	Oval 10 ga. Pan
Blades	1/2" x 4" Heat Treated Alloy Steel Free-Swinging High Lift - Low Friction
Blade Bolt	Keyed with harden flat washer and lock nut
Blade Cutting Capacity	1 1/2" Diameter
Front Guard	Standard: Rubber Guard Optional: Chain Guard
Rear Guard	Standard: Metal Banding Optional: Chain Guard

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Rotary Cutters, Single Deck

RCR1884 Model

Features	Benefits
Surpassed rugged industry standards	All Land Pride Rotary Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
Tractor HP range	45 - 90 HP
5 Year gearbox warranty	Shows our confidence in the gearbox integrity.
Cat. 4 driveline with 2-plate slip-clutch	Slip-clutch driveline offers convenience for continual work.
Cat I or Cat II Hitch Quick Hitch Capability	Permits deck to follow the terrain for an even cut. Quick Hitch provides for fast hook-up.
Lower clevis type 3-point hitch	Allows for ease of hook-up to tractor. Also adds additional strength allowing for an even pull from the tractor's lower arms, vs. pulling on a single pin design.
84" Cutting width	Wide cutting width, Reduces cutting time in the field.
Heavy 10 gauge deck construction	Can withstand more abuse than lighter gauge decks.
Box tubing deck supports	Makes for a stronger rigid deck.
Fully welded deck	Adds additional strength.
Extended front	For increased material flow and added protection.
Round back design	Helps discharge grass better than enclosed or partially enclosed cutters.
9 1 1/2" Deck Height	Allows cutter to handle heavy cutting conditions.
2" to 11" Cutting height	Provides for a wide range of cutting conditions.
Standard rear guard: Metal band	Aids against flying debris.
Optional rear guard: Chain guard	Provides better material discharge relief than metal band guard.
Optional front guard: Rubber guard Chain guard	Aids against flying debris. Provides better protection than the rubber guard.
1/4" x 2 1/2" Full length skid shoes	Provides sidewall reinforcement and full protection to bottom of sidewall.
Splined blade bar hub	Allows for tight positive fit of stump jumper and blade bar to gearbox output shaft.
10 Gauge stump jumper	Standard oval stump jumper slides over stumps, rocks and debris.
High blade tip speed	Ensures clean cut. (17,113 FPM)
15" Laminated tailwheel	Laminated material is long lasting in rough conditions.
Heavy-duty spindle on tailwheel	Tailwheels take a beating, 1 1/4" spindle gives the strength to protect tailwheel assembly.
1 1/2" Cutting capacity	Can aid in cleaning brush
90 Hp gearbox	A rugged heavy built gearbox capable of handling heavy cutting applications.

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.