

Rotary Cutters, Single Deck



<b>RCR2684 Model</b>	
	<b>RCR2684</b>
Cutting Width	84"
Overall Width	90 3/4"
Overall Length (Including Tailwheel)	Single Tailwheel 133" Dual Tailwheel 116"
Blade Tip Speed	540 RPM PTO: 14,369 FPM / 163 MPH
Machine Weight	Single Tailwheel 1370 Dual Tailwheel 1500
Driveline	ASAE Category 4
Slip Protection	4 Plate Slip Clutch
Recommended Tractor HP	60 to 110 HP
PTO Speed	540 rpm
Gearbox	540 RPM PTO Driven 1 3/8" 6-Spline Input Shaft Beveled Gears in Cast Iron Housing
Gearbox Lubrication	80-90W EP oil
Gear box Output Shaft Diameter	2"
Cutting Height	2" - 12"
Deck Material Thickness	10 Gauge
Side Panel Thickness	1/4"
Deck Height	10 1/8" Bottom of deck to bottom of skid.
Deck Construction	All Welded
Skids	Replaceable
Tailwheel Mount Assembly	Welded Arm and Caster Fork.
Tailwheel(s)	Provided with single or dual tailwheels. 4.00 x 8 x 15 1/4 Laminated Tire(s) with Cast Iron Hub and Tapered Roller Bearings.
Hitch	Category II Standard & Category III Adaptable
Stump Jumper	Oval Pan 3/16" x 24" x 38"
Blades (2)	1/2" x 4" x 31" Heat Treated Alloy Steel Free-Swinging High Suction Blades
Blade Bolts	Keyed with Harden Flat Washer and Lock Nut
Blade Cutting Capacity	2"
Optional Front Guard	Chain guard - Standard Rubber guard - Available through parts department.
Optional Rear Guard	Chain guard - Standard

*Designs, specifications, features and information are subject to change without notice.*

*This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.*

**Rotary Cutters, Single Deck**

**RCR2684 Model**

Features	Benefits
Surpassed rugged industry standards	All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
Tractor HP Range	60-110 HP.
5 Year gearbox warranty	Shows Land Pride's confidence in gearbox integrity.
Cat. 4 driveline with 4 plate slip-clutch	Excellent gearbox protection with the slip-clutch slipping when encountering obstruction in the blade path. Standard slip-clutch offers convenience over shear-bolts.
Cat. II or III Three-point hitch	Allows use on a wider variety of tractors.
Available with single or dual tailwheels	Dual tailwheels offer greater stability in uneven terrain.
Cutting width	84"
1/4" Side panels for overall reinforcement	Also protects sides from debris being thrown against them from the blades.
Fully welded deck	Robotically welded. Adds additional strength and deck integrity.
Round back design	Allows for more efficient handling and dispersing of material.
Chain or rubber shield option	Located on front and rear. Reduces flying debris.
Full length skids with replaceable shoes	Full length skids protect side plate structure, replaceable shoes for convenience.
Splined blade bar	Allows for tight positive fit of stump jumper and blade bar to gearbox output shaft.
3/16" Oval stump jumper	Standard stump jumper aids in sliding over obstructions, which helps protect gearbox output shaft.
1/2" x 4" Heat-treated free swinging blades	Free swinging protects from obstructions. Heat-treated offers longer life.
2" Diameter cutting capacity	Can aid in clearing brush.
High blade tip speed	14,369 fpm
Rugged laminated tailwheel	Can't go flat.

*Designs, specifications, features and information are subject to change without notice.*

*This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.*