

Box Scrapers



HR35 & MR35 Retractable Series (Highback)

	3572	3584
Working Width	72"	84"
Capacity (Cubic/Foot)	27	31
Weight (Pounds)	990	1117
Weight (with hydraulics)	994	1119
Number of Shanks	8	8
Shank Material	3/4" x 2 1/2" heat treated spring steel	
Shank Penetration	3- positions (2", 3" & 5" below scraper end plates)	
Shank Tip Construction	Replaceable heat treated tips	
Shank Beam	Pivots to lift shanks up; transport lock on shank tube Series HR35: Hydraulic lift Series MR35: Manual lever lift with spring assist.	
Height of Moldboard	24"	
Side Plates	1/2" thick x 24" high x 30" deep	
Overall Depth	41"	
Grader Blades	1/2" x 6" high carbon, heat treated cutting edges; reversible and replaceable	
Maximum H.P. Rating	65	
Hitch Point Construction	Harden bushings in upper and lower hitch points	
Hitch Type	Category I & 2	

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Box Scrapers



HRL35 & MRL35 Retractable Series (Lowback)

	3572	3578
Working Width	72"	78"
Capacity (Cubic/Foot)	23	26
Weight (Pounds)	931	972
Weight (with hydraulics)	937	981
Number of Shanks	8	8
Shank Material	3/4" x 2 1/2" heat treated spring steel	
Shank Penetration	3- positions (2", 3" & 5" below scraper end plates)	
Shank Tip Construction	Replaceable heat treated tips	
Shank Beam	Pivots to lift shanks up; transport lock on shank tube Series HRL35: Hydraulic lift Series MRL35: Manual lever lift with spring assist.	
Height of Moldboard	19"	
Side Plates	1/2" thick x 19" high x 30" deep	
Overall Depth	41"	
Grader Blades	1/2" x 6" high carbon, heat treated cutting edges; reversible and replaceable	
Maximum H.P. Rating	65	
Hitch Point Construction	Harden bushings in upper and lower hitch points	
Hitch Type	Category I & 2	

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Box Scrapers

HR35 & MR35 Series (Retractable)

Features	Benefits
Manual or hydraulic shank tube	Retractable mode can be purchased with manual or hydraulic option.
Available in high or low back design.	Can match up to any type of work or tractor capacity.
Knurled bushings in upper and lower hitch	Work done with retractable box blades is done forwards and backwards. Bushings at hitch points eliminate premature wear.
3 Position heat treated spring steel shanks	Positions set for deep to shallow settings. Heat-treated for longevity.
Shank bumper	3/4" Steel bumper is located behind each shank for reinforcement.
Heat treated dimpled on tips	Easy to replace tips are heat treated for toughness.
Hinged rear backfill blade. Fixed or floating	Rear backfill blade can be in float or fixed position. For packed down grade, level grade or rough grade
1/2" Side panels	Thick end panels guard against abrasion.
Working widths	72", 78", 84"
HP Range	40-65 HP
Cat. 1 & 2	Fits a wide variety of tractors.
Roll-formed moldboard: 24" high back, 19" low back	Roll-formed moldboard keeps materials flowing which puts less drag on the box scraper, resulting in lower HP requirements and faster working conditions.
Heat-treated, reversible and replaceable cutting edges	Heat-treated for hardness. Reversible so both edges can be used before having to be replaced.
Transport lock on shank tube	Heavy-duty shank lock to keep shanks locked into place during transport.
Warranty	One year parts & labor.

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.