

Disc Harrows



DH15 and DH25 Series

	DH1560	DH1572	DH2572
Hitch	Cat. 1 (Fits Land Pride Quick Hitch)		Cat. 1 & Cat. 2
Cutting Width	60"	72"	72"
Height	40"		41 1/2"
Length	56"	56 1/2"	84 1/2"
Weight	628 lbs.	714 lbs.	947 lbs.
Weight load on each Disc	38 lbs.	34 lbs.	59 lbs.
No. of disc blades	16	20	20
Disc Blade size	18" Diameter notched or smooth		20" or 22" Diameter
Disc Blade spacing	7 1/2"		
Bearing Hanger	3/8" plate, 2 each 5/8" U-bolts		1/2" plate, 2 each 5/8" u-bolts
Bearing Type, 2 per gang			
Disc Angle	Front & rear gang: 0, 7, 14, & 21 degrees		Front gang: 0, 7, 14, & 21 degrees with angling adjustment handle Rear Gang: 7, 14 & 21 degrees With angling adjustment handle
Frame Tubes	2 1/2" square		3" square
Gang Tube	3" x 2"		4" X 3"
Gang Axle	1" square high carbon steel		1 1/8" square high carbon steel
Disc Scrapers	Optional, Adjustable		Optional, Adjustable
9" Center Sweep	Optional, Removes Center Ridge		

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Disc Harrows

DH15 Series

Features	Benefits
Working widths	60", 72"
3-point Hitch	Cat. 1 (Fits Land Pride Quick-Hitch for easy one-person attachment and removal.)
Weight	60" - 629 lbs.; 72" - 714lbs. Heavy construction helps penetrate ground.
2 1/2" Square frame tube	Frame tubing is stronger than angle iron.
Adjustable gang angles	Cutting aggressiveness can be adjusted on the front and rear up to 21 degrees.
Adjustable gang handles	Gives the user something to hold on to while adjusting gang angles.
3" x 2" Gang tube, 1" Square gang axles, high carbon steel	High carbon square axles offer great strength in punishing conditions.
18" Notched or smooth disc blades	Choose notched blades for more aggressive digging and cutting action, or the smooth blades for light tilling.
3/8" Thick bearing hangers with two 5/8" U-bolts	Heavy-duty hangers resist the high torque from U-bolts and/or keep the discs out of the ground.
1/2" Frame side plates	Offer additional strength and reinforcement to the gang tube.
Self aligning sealed bearings	Self-aligning bearings offer long life while pounding through hard ground.
Optional scrapers	Scrapers will clean the discs off which can plug up and/or keep the discs out of the ground.

DH25 Series

Features	Benefits
Working widths	72", 96"
Cat. 1 & 2 3-point hitch	Fits a wide variety of tractors.
Quick-Hitch compatible	Fits Land Prides Quick-Hitch for easy one-person attachment and removal.
Weight	72" = 947 lbs.; 96" = 1143 lbs. Heavy construction helps penetrate ground
3" Square frame tube	Heavy frame can handle 100 HP tractors.
Ball bearings	Self-aligning, sealed ball bearings.
Adjustable gang angles	Vary the degree of aggressiveness on both front and rear gangs.
Gang adjustment handle	Gives the user something to hold on to while adjusting the gang angles.
4" x 3" Gang tube	The gang tube resists twisting due to 4" horizontal width.
1 1/8" Square gang axles	Large axles can resist the high load put on them as the discs roll through the ground.
20" or 22" Notched disc blades	Larger discs will penetrate harder ground.
1/2" Thick bearing hangers	1/2" Thick bearing hangers resist high torque.

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.