

Flail Mowers



FM2060 & FM2072 Series Flail Mowers		
	FM2060	FM2072
Cutting Width	60"	72"
Overall Width	68"	80"
Height	37"	
Depth	28"	
Weight	616 lbs.	660 lbs.
Cutting Height	0-4"	
Cutting Capacity	1"	
Deck Material Thickness	11 gauge	
Knives	Fine cut	
Rotor Shaft Speed	1980 RPM	
Rotor Diameter	4 1/4"	
Rotor Rotation	Reverse	
Knife Tip Speed	8705 fpm	
Number of Knives	60	72
Hitch Type	Category I	
Offset Hitch	6 1/4"	
PTO Speed	540 RPM	
Driveline	Cat 4 w/Over-running Clutch	
Gearbox Rating	55 HP	
Drive Belts	(2) - "B" Section Belts	
Rear Roller Diameter	5 1/2"	

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Flail Mowers

FM20 Series

Features	Benefits
Key widths	60", 72"
6 1/4" Right, centered offset hitch	The two position hitch for offsetting the mower allows closer cutting along buildings, fences or roadsides.
Gearbox HP rating	25 - 55 HP to fit a large array of tractors
0" – 4" Cutting height	Low cutting height allows for scalping in grasses such as Bermuda prior to overseeding.
Gearbox Warranty	One year on all components
1" Cutting capacity	Can cut small saplings.
4 1/4" Rotor diameter	Large rotor diameter protects against obstructions.
Reverse rotor rotation	Reverse rotation brings the cut grass up and over the rotor for a cleaner discharge.
Cat. 4 driveline with over-running clutch	Upon disengaging the PTO, the over-running clutch allows the driveline to quit turning, while the clutch yoke, gearbox and rotor shaft slow down by their own inertia.
3 - "B" Section belts	"B" Section belts fit snug in the sheaves, and the multiple belts ensure positive transfer of power.
3 Fine cut knives per hanger	Helps eliminate the peak and valley cut left with many fine cut blade arrangements.
High knife tip speed	Knife tip speed of 8,705 fpm for cleaner cut.
Adjustable rear panel	Rear panel adjusts to allow stronger discharge of material. Also aids in cleaning underside of deck.
Baffles on the top inside of the deck	Keeps the cut material from clumping together, ensuring an even distribution of clippings.
Height adjusting roller	Rear height adjusting roller with greaseable bearings and tapered ends to prevent gouging during turns.
Scrapers	Standard scrapers on rear height adjusting roller.

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.