

Rotary Cutters, Folding Deck

RC5515, RCM5515 RC6515 & RCM6515

	RC5515 & RCM5515	RC6515 & RCM6515
Gearbox Horsepower	250 HP Splitter 210 HP Center & Wing	250 HP Splitter 210 HP Center & Wing (Blade spindle gearboxes are built heavier)
Cutting Capacity	3 1/2"	4"
Machine Weight	Single row chain guards, 6 laminated wheels, 540 CV main driveline & standard clevis hitch 5,300 lbs. Approx. 5,323 lbs. Approx.	
Blade Tip Speed	At 540 RPM: Center Blades = 14,886 FPM Wing Blades = 14,769 FPM At 1000 RPM: Center Blades = 15,604 FPM Wing Blades = 15,741 FPM	
Hitch Weight	1,860 lbs.	
Hitch Type	Pull Type, Self - Leveling Hitch & Clevis Clevis Type: Standard, Up & Down Swivel	
Hitch Jack	Standard	
Cutting Width	15'-0"	
Overall Width	15'-8"	
Minimum Transport Width	8'-0"	
Overall Length	15'-1"	
Deck Height	12"	
Cutting Height	2" to 14"	
Lift Hydraulics	3 1/2" x 8" hydraulic cylinder, hoses, fittings & stroke control spacers	
Wing Hydraulics	3" x 12" hydraulic cylinders, hoses & fittings	
Wing Transport Protection	Wing Transport Locks	
Deck Material	10 gauge Top Deck and 7 gauge Bottom Deck	
Side Skirt Material	Bolt-on replaceable 1/4" side	
Skid Shoes	Wing: Reversible & replaceable Center Deck: 2 with optional mounting location on center deck	
Blades - 6 (2 per Carrier)	1/2" x 4" Heat Treated Free Swinging Alloy Steel with up lift	
Blade Overlap	6"	
Blade Bolt	Keyed with hardened flat washer & lock nut	
Stump Jumper / Blade Holder	3/16" Round dish shaped pan, reinforced with 1" x 5" x 22 3/4" blade bar	
Deck Ring	Optional 1/2" x 3" fully welded	
Front & Rear Guards	Optional rubber, single chain or double chain	
Input Driveline	ASAE Category 5 Star Profile with constant velocity u-joint or conventional (non-cv) u-joint.	
Wing Drivelines	ASAE Category 4 star profile with slip-clutch, or optional Cat. 5 with slip-clutch	ASAE Category 5 star profile with slip-clutch
Wheel Options	6" x 21" Laminated Tires or 15" Rims or 24" x 7.75" x 15", Used Aircraft Tires with or without foam filling	
Number of Wheels	6 - Wheel option: 4 on transport axle and one on each wing axle 8 - Wheel option: 4 on transport axle and two on each wing axle.	
Transport Axle	Spring-cushioned on center transport axle optional Walking tandem	
Hubs	Cast iron five-bolt hubs with tapered roller bearings and 1 3/4" shafts.	
Min. PTO Horse Power	50	
Colors	Standard color: Beige; Optional colors: Green or Red	

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Rotary Cutters, Folding Deck

RC(M)5515 & RC(M)6515 Models	
Features	Benefits
Surpassed rugged industry standards	All Land Pride Cutters have been designed and tested and meet rigorous voluntary testing procedures specified by ANSI.
Factory assembled	Saves customer set-up time and money.
5 Year gearbox warranty	Shows confidence in gearbox integrity.
Gearbox Seal Protection	Gearbox bottom seal protection for longer bearing life.
2 3/8" Output gearbox shaft	Large output shaft handles shock loads better.
250 HP Splitter gearbox	High gearbox rating for rough work and high horsepower tractors.
210 HP center & wing gearboxes 55 Series 65 Series	High gearbox rating for 3 1/2" cutting capacity and high horsepower tractors. Higher gearbox rating for 4" cutting capacity and high horsepower tractors.
540 or 1000 RPM PTO speed	Fits wide variety of tractors.
Input driveline: Cat. 5 CV	Holds up to shock loads and harsh mowing conditions.
Star profile drive shafts	Star profile spreads load out to many points on the shaft. More apt to resist bending and twisting under shock loads and harsh mowing conditions.
Easy Greasable drivelines	Drivelines have access holes for greasing the U-joints in the driveline and to grease the inner profiles.
4 Plate slip-clutch	Protects drivelines and gearboxes by slipping clutches rather than twisting the driveline when impacts are encountered.
High blade tip speed	Allows clean cutting of material.
6" Blade overlap	Eliminates skipping during turns.
High cutting capacity 55 Series 65 Series	Can cut brushy areas with saplings up to 3 1/2". Can cut brushy areas with saplings up to 4".
12" Deck height	Handles heavy cutting, which reduces balling-up of cut material under the deck.
Left wing rotates clockwise	Better discharge of material. Picks up tractor tracks.
2 to 14" Cutting height	Covers a wide range of cutting conditions.
3/16" Stump jumper backed with a 1" thick mounting bar	Heavy round stump jumper with bottom gearbox seal protector. Can hold up to tough conditions.
10 gauge smooth deck top	Reduces accumulation of debris and is easier and faster to clean.
7 Gauge smooth deck bottom	Heavy deck design holds up to harsh conditions. No bottom obstructions.
Deck rings (option)	Keeps blades from damaging the deck.
Replaceable 1/4" wing sidewall	Reduces debris piercing possibilities. Can be replaced if damaged.
Reversible / Replaceable skid shoes	Can be reversed for extended life and can be replaced when damaged or worn out.
Self-leveling hitch	Reduces drawbar wear by keeping hitch level while going through ditches.
Hinged wing sections	Allow you to shape the cutter to the job. Ideal for rough ground where hillsides, ditches and hollows can cause uneven cutting.
1" Solid hinge rods	Larger diameter hinge rod gives greater strength to the cutter from front to rear, and in the hinge area itself.
Wing transport locks	Holds transport wings in the folded-up position in case of hydraulic pressure loss.
Enclosed front to rear dual leveling rods	Dual leveling rods enable the cutter to pull equally on the rear axle during travel over rough terrain. Many competitors only use one leveling rod.
5-Bolt hubs	5-Bolt hubs makes the wheel assembly more durable and longer lasting.

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Rotary Cutters, Folding Deck

RC(M)5515 & RC(M)6515 Models	
Features	Benefits
Drain holes in wheel rims	Allows water to drain from wheels mounted on folded-up wings. Helps prevent paint deterioration and rusting to the wheel rims.
Spring-cushioned center-axle	Protects unit from bumps and ground shock.
Replaceable wheel spindles	Wheel spindles can be replaced when damaged without replacing the entire axle. Simply remove two bolts to replace damaged spindle.
Features and Benefits Of Optional Equipment	
Double swivel hitch	Great for uneven terrain, reduces drawbar wear.
Bar-tite clevis hitch	Ideal hitch for extreme conditions. Clamps tight to the drawbar eliminating any drawbar wear.
Wheels	6 or 8 wheel option.
Airplane tires	Airplane tires give better cushion while transporting the cutter.
Laminated tires	Can't go flat.
Walking Tandem	Better flotation and smoother ride on rougher terrain.

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.