

Rear Blades



RBT35 Series		
	RBT3572	RBT3584
Blade Width	72"	84"
Approximate Weight (lbs.) w/manual links	672	709
Maximum Engine Horsepower	80 HP for 2 Wheel Drive and 65 HP for 4 Wheel Drive	
Maximum G.V.W. (lbs.)	9500	
Hitch Type	Cat. 1 & 2 Fits Land Pride Quick-Hitch	
Blade Angle	Manual:	9 positions in 10 degree increments (1 center, 4 clockwise & 4 counterclockwise)
	hydraulic:	Up to 50 degrees in either direction.
Angle Cylinder	3 1/2" X 14" X 1 1/4"	
Blade Tilt	Up to 20 degrees	
Tilt Cylinder	2" X 6" X 1 1/4"	
Blade Offset	Up to 30 inches left and right	
Offset Cylinder	3 1/2" X 14" X 1 1/4"	
Moldboard Height	17" tall	
Moldboard Thickness	5/16" reinforced, 3/16" tapered reinforcement channel	
Moldboard King Pin	3" diameter	
Cutting Edge	1/2" x 6" Heat reversible blade	
Main Frame Construction	Fully Welded Tubular Construction	
Parking Stand	Retractable	
Accessories	Skid Shoes End Plates Gauge Wheel Cushion Valve	

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Rear Blades

RBT35 Series

Features	Benefits
HP Rating	35 to 80 HP (2 wheel drive tractors)
3 Way Blade	Tilt, angle and offset features available hydraulically or manually.
Angle	Manual: 10 Degree Increments up to 40 degrees Hydraulic: Up to 50 degrees.
Offset	Up to 30" left and right.
Tilt	up to 20 degrees.
17 inch Moldboard	Precisely formed moldboard rolls dirt and debris with ease.
3" Moldboard King pin	Heavy pin for its class of blade.
Working widths	72", 84", and 96"
Cat. 1 or 2	Fits wide variety of tractors.
Fits Land Pride Quick-Hitch	Quick and easy attaching without leaving tractor seat.
5/16" Moldboard thickness with box reinforcement	Thick material with fully welded box reinforcement creates a strong moldboard.
Fully welded main frame (Tubular construction)	Fully welded adds overall strength and rigidity to blade frame.
Retractable parking stand	Able to store the unit with the frame off the ground, also aids in attaching to tractor.
Reversible cutting edge	Get twice the wear from the cutting edge by flipping it over.
Warranty	One year parts & labor. See warranty page for complete details.
Accessories	
Skid shoes	Skid shoes help protect from hitting low obstructions by keeping the moldboard off the ground.
Cushion valve	Helps protect the moldboard and cylinders in the event an obstruction is hit by allowing hydraulic fluid to bypass the cushion valve and flow back towards the tractor.
Side plates	Side plates hold material in and allows it to be moved.
Skid shoes	Skid shoes help protect the blade and the surface the blade is cleaning.
Side Plates	Plates hold in extra material.

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.