

**Rotary Tillers**



<b>RTR2570 Model</b>	
<b>Hitch</b>	Category 1
<b>Width</b>	70"
<b>Overall Width</b>	76"
<b>Weight</b>	868
<b>Number of Flanges</b>	9
<b>Number of Tines per Flange</b>	6
<b>PTO Driveline</b>	ASAE Category III Heavy Duty Friction Clutch-Standard
<b>Gearbox</b>	45 HP Input at 540 rpm 1.92:1 Ratio Cast Iron Housing, Straight Bevel Gears
<b>Gearbox Lubrication</b>	Gear Lube 80-90W EP
<b>Drive Chain</b>	#100 roller chain in flowable grease bath
<b>Drive Chain lubrication</b>	Shell Alvania EP 00
<b>Sprockets</b>	Splined Bores
<b>Rotor Swing Diameter</b>	17"
<b>Rotor Shaft Speed</b>	220 rpm at 540 rpm PTO

*Designs, specifications, features and information are subject to change without notice.*

*This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.*

**Rotary Tillers, Reverse Tine Rotation**

**RTR2570 Model**

Features	Benefits
Tractor HP rating	25-55 HP
Gearbox Warranty	3 Years on housing, gears, shafts, seals, bearings. Shows our confidence in the product.
Fits Land Pride Quick-Hitch	Allows for quick and easy one person hook-up. Cannot be used with offset.
Reverse tilling action	Reverse action 'sucks' tiller into ground, does not walk on top of hard ground like forward rotation tillers can.
Offset capability	Offset 5" by moving lower hitch points, allows to cover right tire track.
Parking stand	Allows for easy hook-up and storage.
Stamped top hitch	Stamped plate adds additional strength to hitch.
Hitch bolted to inside of support	Force is applied downward on top hitch, by bolting hitch to inside of support, keeps hitch from spreading outward.
Six tines per flange	Six tines go through the ground better than four.
17" Rotor swing diameter	For deep tilling action.
Double lip seal on rotor bearing	Double lip seal keeps the dirt out and the grease in.
#100 Drive chain enclosed in oil bath	Heavy-duty drive chain reduces stretching. Oil keeps constant lubrication and holds wear to a minimum.
Easy to adjust chain tightener	Cast iron chain tightener is a simple bolt adjustment to keep constant tension on the chain.
Adjustable skid shoes	Control depth from various settings.
Stamped chain cover	Stamped forming adds additional strength.
Wear shield on left skid shoe	Shield protects lower portion of chain cover from wearing due to dragging in the soil.
Cat. 3 driveline with slip-clutch	Standard heavy driveline for rough conditions. Slip-clutch protects other drive train components.
Spring tines behind tilling action	Spring tines sift the material letting bigger items fall first. Sifted soil falls last burying the bigger items.
Formed rear deflector with springs	Formed steel gives the rear deflector additional strength. Springs allow deflector to bounce as it hits obstructions.
Front deflector plate	Front deflector plate is flexible to take the beating rocks or debris will give it.

*Designs, specifications, features and information are subject to change without notice.*

*This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.*