

**Soil Pulverizer**

**SP3072 & SP3084**

|   | <b>SP3072</b>   | <b>SP3084</b> |
|---|---|---------------|
| <b>Width</b>                              | 72"   | 84"           |
| <b>Weight (With Single Roller- lbs.)</b>  | 671   | 721           |
| <b>Max Engine Hp.</b>                     | 50 Hp.  | 50 Hp         |
| <b>Number Of Shanks</b>                   | 25  | 29            |
| <b>Number Of Spikes - Single Roller</b>   | 103   | 116           |
| <b>Number Of Spikes - Double Roller</b>   | 206   | 232           |
| <b>Height</b>                             | 36 1/2"   |               |
| <b>Front To Back Length Single Roller</b> | 27 1/4"   |               |
| <b>Front To Back Length Double Roller</b> | 35 1/4"   |               |
| <b>Shank Spacing</b>                      | 2 13/16"  |               |
| <b>Spiked Roller Tube Diameter</b>        | 6 5/8" O.D. (Optional Second Roller 5 9/16")          |               |
| <b>H-Beam</b>                             | 12"   |               |
| <b>A-Frame</b>                            | 3/8" Plate  |               |
| <b>Springs-Front Roller</b>               | 32 lbs./inch  |               |
| <b>Springs - Rear Roller</b>              | 15 lbs./inch  |               |
| <b>Spike Material</b>                     | 3/8" x 1 1/4" Steel, Replaceable Heat Treated Sleeves |               |
| <b>Hitch</b>                              | Cat. 1  |               |

*Designs, specifications, features and information are subject to change without notice.*

*This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.*

**Soil Pulverizers**

**SP30 Series**

| Features  | Benefits  |
|---|---|
| Working widths  | 30 Series: 72", 84"   |
| HP Range  | 30 Series: 30-50 HP   |
| Replaceable heat-treated sleeves                            | Heat-treated replaceable sleeves on roller protect spike. Easily replace the sleeve when worn vs. replacing entire spike. |
| 3/8" Steel spikes welded to the roller's surface            | Spikes are welded to the roller's surface rather than to a hole. Damaged spikes can be cut off and replaced.              |
| Self-aligning bearings with double lip seals on rear roller | Self-aligning bearings conform to the roller and shafts.  |
| 1" Diameter shaft in roller                                 | Heavy shaft can handle the shock loads from the roller.   |
| Roller has high number of steel spikes                      | Better pulverization, more spikes than most competitors   |
| H Beam  | 30 Series: H Beam-12"   |
| 10 1/2" x 2" x 2 1/2" Scarifier teeth                       | Scarifier teeth are heat-treated for long life and can be reversed when one side wears down.                              |
| Warranty  | One year parts and labor  |
| Fits Land Pride Quick-Hitch                                 | Cat. 1 3-point fits Land Pride Quick-Hitch for easy on-off with one person.   |

*Designs, specifications, features and information are subject to change without notice.*

*This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.*