

Box Scrapers



HR25 Series (Retractable)

	HR2560	HR2566	HR2572
Working Width	60"	66"	72"
Weight (Pounds)	743	797	851
Number of Shanks	5	6	7
Shank Penetration	2-positions (3/4" & 3 1/4" below end plates)		
Lift Mechanism	Hydraulic cylinder pivots shank tube to lift shanks up		
Side Plates	3/8" thick x 21" high x 34" deep		
Overall Length	41" (Front to back)		
Height of Moldboard	21"		
Shank Material	3/4" x 2 1/2" heat treated spring steel		
Shank Tip Construction	Replaceable heat treated tips		
Grader Blades	1/2" x 6" high carbon, heat treated cutting edges; reversible and replaceable		
Maximum H.P. Rating	50 HP for 4-wheel drive tractors 60 HP for 2-wheel drive tractors		
Hitch Type	Category I & Quick Hitch		

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Box Scrapers

HR25 Series (Retractable)

Features	Benefits
Mechanical or hydraulic shank tube	Retractable mode can be purchased with manual or hydraulic option.
Available in (HR25 Series) or (HR15 & MR 15 Series).	Can match up to many types of work or tractor capacities.
Heat treated spring steel shanks	Heat-treated for longevity.
Positive Locking System	Shanks are kept in the up or down position with a positive locking system. This keeps the scarifier bar from bouncing in transport, and tight during field use.
Heat treated dimpled on tips	Easy to replace tips are heat treated for toughness.
Rear backfill blade	Rear backfill blade allows for backfilling trenches or foundations.
Working widths	HR15 = 48", 54" & 60" Various working widths to MR15 = 48", 54", 60" & 72" match many tractor sizes. HR25 = 60", 66" & 72"
Quick Hitch or Cat. 1 3-Point Hitch	Fits a wide variety of tractors. Quick hitch capability allows for easy hook-up.
Lower hitch clevises	Allows for easier hook-up of the tractor's lower draft arms.
Roll-formed moldboard: 19" high HR15 & MR15 21" high HR25	Roll-formed moldboard keeps materials flowing which puts less drag on the Box Scraper, resulting in lower HP requirements and faster working conditions.
Heat-treated, reversible and replaceable cutting edges	Heat-treated for hardness. Reversible so both edges can be used before having to be replaced.
Warranty	One year parts & labor.

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.