

Landscape Rakes



LR25 & LR35 Series				
	LR2584	LR2596	LR3584	LR3596
Rake Width	84"	96"	84"	96"
Approximate Weight (lbs.)	352	377	460	483
Horsepower Rating	25 - 50		30-65	
Hitch Type	Cat. I Fits Land Pride Quick Hitch		Cat. I & II Fits Land Pride Quick Hitch	
Angle/Position	5 Forward / 5 Reverse Up to 45 degrees right or left		9 Forward / 5 Reverse Up to 60 degrees right or left	
Rake Height	15 1/4"		16 1/2"	
Number of Teeth	42	48	42	48
Teeth Spacing	1" Opening			
Teeth Material	High Carbon Steel			
Teeth Size	5/16" x 1" Wide			
Options	Dual Gauge Wheels; Flip-Down Grader Blade; Hydraulic Angle Kit		Dual Gauge Wheels; Flip-Down Grader Blade;	
Offset (Manual/Hydraulic)	N/A		45 degrees left or right	
Tilt	N/A		5 positions to 30 degrees	

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Landscape Rakes

LR25 Series

Features	Benefits
Working widths	84", 96"
HP Range	25-50 HP
Fits Land Pride Quick-Hitch	Allows for quick and easy one person hook-up.
Angle 7 forward positions and 5 reverse positions	Vary amount of material to move.
Optional hydraulic angle cylinder	Change the rake angle on the go from the tractor seat.
16 1/2" Rake height	Allows for moving a great deal of material.
High carbon spring steel teeth	Allows teeth to keep their shape.
Individually replaceable teeth	Makes replacement easy and quick.
Retractable Parking Stand	Keeps the frame off the ground and makes hook-up easier.
Single or dual gauge wheels (optional)	Depth control.
Flip-down grader blade and end plates (optional)	Allows rake to be used for leveling by being able to scrape and drag material.
Blade adaptable	Adds versatility.
Warranty	One year parts & labor.

LR35 Series

Features	Benefits
Working widths	84", 96"
Tractor HP Range	30-65 HP
Cat. I & II	Fits a wider variety of tractors.
Fits Land Pride Quick-Hitch	Allows for quick and easy one person hook-up.
Frame offsets 45 degrees manually or hydraulically	Easily cover one tractor tire track. Optional hydraulic provided control from the tractor seat.
Angle 9 forward positions and 5 reverse positions	Vary the amount of material being moved.
16 1/2" Rake height	Can move a great deal of material.
High carbon spring steel teeth	84" width = 42 teeth 96" width = 48 teeth Allows teeth to keep their shape.
Individually replaceable teeth	Quick and easy replacement.
Retractable Parking Stand	Keeps the frame off the ground and makes hook-up easier.
Rear Blade adaptable	Get more out of a rake investment.
Single or dual gauge wheels (optional)	Provide better depth control.
Flip-down grader blade and side plates (optional)	Enables the rake to perform light blading duties and can be flipped up when not in use.
Warranty	One year parts & labor.

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.