

Post Hole Diggers



PD10, PD15, PD25 and PD35 Series	
	PD10
Tractor HP	30 HP
Flighting Thickness	1/4"
Auger Dia.	6", 9", and 12" Cast fishtail tip, hardened reversible cutting teeth
Hitch Cat.	I
Boom Tube	2 7/8" O.D.
Yoke Tube	2 7/8" O.D.
Driveline Cat.	II
Gearbox	540 RPM 3:1 Ratio, Operating RPM: 300
Weight	120 lbs (without Auger).
	PD15
Tractor HP	40 HP
Flighting Thickness	1/4"
Auger Dia.	6", 9", and 12" Cast fishtail tip, hardened reversible cutting teeth
Hitch Cat.	I
Boom Tube	2 7/8" O.D.
Yoke Tube	2 7/8" O.D.
Driveline Cat.	II
Gearbox	540 RPM 3.18:1 Ratio, Operating RPM: 300
Weight	161 lbs. (without Auger)
	PD25
Tractor HP	55 HP
Flighting Thickness	1/4"
Auger Dia.	6", 9", 12", 14", 18", and 24" Cast fishtail tip, hardened reversible cutting teeth
Hitch Cat.	I - II
Boom Tube	3 1/2" O.D.
Yoke Tube	2 7/8" O.D.
Driveline Cat.	III Shear bolt - Standard III Radial pin clutch - Optional
Gearbox	540 RPM 3.18:1 Ratio, Operating RPM: 300
Weight	186 lbs. (without Auger)
	PD35
Tractor HP	75 HP
Flighting Thickness	1/4"
Auger Dia.	6", 9", 12", 14", 18", and 24" Cast fishtail tip, hardened reversible cutting teeth
Hitch Cat.	I - II
Boom Tube	3 1/2" O.D.
Yoke Tube	2 7/8" O.D.
Driveline Cat.	III Shear bolt - Standard III Radial pin clutch - Optional
Gearbox	540 RPM 4:1 Ratio, Operating RPM: 300
Weight	233 lbs. (Without Auger)

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Post Hole Diggers, PTO

PD10 Series

Features	Benefits
Shorter yoke and boom tubing	Allows post hole digger to be used on sub compact utility tractors (i.e. BX Kubota).
Auger length	30" Auger.
Auger flighting	1/4" Flighting, Semi-double flight.
Cast steel auger fishtail tips	Fishtail tip is an excellent pilot point to get hole started.
Gearbox	15 to 30 HP Horsepower (2" output shaft).
Gearbox warranty	5 Years.
2 7/8" Yoke tubing	Same as our 15 Series Post Hole Digger.
Down pressure kit (optional)	Allows additional down force to be supplied to beam to help force digger into the ground.
Alignment handle (optional)	Helps guide the auger from the tractor seat.
Post Hole Digger stand (optional)	Bracket mounted to bottom of gearbox can incorporate a post hole digger stand. This allows operator to hook up and unhook from tractor more safely. Stand supports unit and will store unit when it is not on the tractor.

PD15 Series

Features	Benefits
2 7/8" Yoke tubing	3/16" Wall thickness for strength.
Auger length	48" Auger.
Auger flighting	1/4" Flighting, Semi-double flight.
Cast steel auger fishtail tips	Fishtail tip is an excellent pilot point to get hole started.
Gearbox	20 to 40 HP Horsepower (2" output shaft).
Gearbox warranty	5 Years.
Down pressure kit (optional)	Allows additional down force to be supplied to beam to help force digger into the ground.
Alignment handle (optional)	Helps guide the auger from the tractor seat.
Post Hole Digger stand (optional)	Bracket mounted to bottom of gearbox can incorporate a post hole digger stand. This allows operator to hook up and unhook from tractor more safely. Stand supports unit and will store unit when it is not on the tractor.

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.

Post Hole Diggers, PTO

PD25 & PD35 Series

Features	Benefits
2 7/8" Yoke Tubing	3/16"+ Wall thickness for strength.
3 1/2" Reinforced boom tubing	7/32" Wall tubing for strength.
Auger flighting	Constant thickness on flighting vs. tapered.
Replaceable hardened steel points on auger	Hardened points will last longer than non-hardened. Points can easily be replaced when worn or damaged. Cast steel auger fishtail tips.
Gearbox HP rating	25 Series: 25-55; 35 Series 30-75 HP.
5 Year gearbox warranty	Shows our confidence in the gearbox integrity.
2" Output shaft	Fits most other auger manufacturers for users who don't need a new auger.
Cat. 3 driveline with shear-pin and radial pin	Protection against obstructions. Radial pin works like a 'ratchet' to continually put driving force on the auger in tough conditions.
Alignment handle (optional)	Guide the auger from the tractor seat.
Down pressure kit (optional)	Allows additional force to be supplied, hydraulically, to the beam to help force digger into the ground.
Post Hole Digger stand (optional)	Bracket mounted to bottom of gearbox can incorporate a post hole digger stand. This allows operator to hook up and unhook from tractor more safely. Stand supports unit and will store unit when it is not on the tractor.

Optional Features (PD Support Stand)

Features	Benefits
Fits existing and current Land Pride Post Hole Diggers	Can be purchased for older models.
Quick disconnect	Easy on and off design.
3 Point hook up	Design makes it possible to back up to the post hole digger with a tractor and hook up and disconnect with ease and safety.
Storage capabilities	Digger stand allows post hole digger to be stored safely and efficiently. The stand allows easy hook up in future use.

Designs, specifications, features and information are subject to change without notice.

This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgement to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.