

Rotary Cutters, Single Deck

RCR35 Series

	RCR3510 (540 RPM) RCRM3510 (1000 RPM)
Machine Weight With Front Guard	Lift-Type 1825 lbs.
Hitch	Lift-Type & Semi-Mount Category 2 & 3 Quick-Hitch adaptable Pull-Type - w/Dual Self Level Rods
Cutting Width	10'
Overall Width	10' 5"
Overall Length	Lift - 110" Semi - 118" Pull - 145"
Deck Height	9 5/8"
Cutting Height	2" - 10 1/2" 2" - 12"
Cutting Capacity	2"
Tractor H.P. Rating (PTO)	Lift-Type - 60 - 120 Pull/Semi - 50 - 120
Gearbox Rating H.P.	Center - 120 HP, Outboard 100 HP
Gearbox	540 rpm or 1000 rpm PTO Driven Gearbox Cast Iron Housing, Beveled Gears
Gearbox Lubrication	80-90W EP Gear Lube
Gearbox Input/ Output Shaft Size	Input Shaft = 1 3/4" - 20 Spline Output Shaft = 2" Dia.
Deck Material Thickness	10 gauge
Deck Side Skirt Thickness	1/4"
Skids	Replaceable
Stump Jumper	Round Pan 3/16"
Blades (4)	1/2" x 4" Heat Treated Free-Swinging Suction Blades
Blade Bolts	Keyed with Harden Flat Washer and Lock Nut
Blade Tip Speed	540 RPM 17,291 fpm 1000 RPM 17,569 fpm
Driveline	ASAE Cat 4 with Equal Angle Shaft or Constant Velocity U-Joint on Pull Type
Driveline Protection	540 rpm - 4 plate slip clutch 1000 rpm - 2 plate slip clutch
Tailwheel	Semi-Mount: Lift-Type: 8' Pull-Type: 10' Pull-Type:
Wheel Bearings	2 ea. 6" x 9" x 21" Laminated 2 ea. 4" x 8" x 15 1/4" Laminated 2 ea. 6" x 9" x 21" Laminated or 24" Aircraft tires or 5" x 15" Automotive Rims 2 or 4 ea. 6" x 9" x 21" Laminated or 24" Aircraft tires or 5" x 15" Automotive Rims
Front Guard	Tapered Roller Bearing in Cast Iron Hub
Rear Guard	Optional: Chain guard or Rubber deflector
Shock Absorption	Optional: Chain guard or Rubber guard
Jack Stand	Spring Shock Absorber on Axle of Pull Type
	Jack Stand on Tongue of Pull Type Cutter

Designs, specifications, features and information are subject to change without notice. This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgment to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride *Warranties*.

Rotary Cutters, Single Deck

RCR35 Series

	RCR3596 (540 RPM) RCRM3596 (1000 RPM)
Machine Weight With Front Guard	Lift-Type 1347 lbs.
Hitch	Lift-Type & Semi-Mount Category 1 & 2 Quick hitch adaptable Pull-Type - w/Dual Self Level Rods
Cutting Width	8' -2"
Overall Width	8' 6 1/2"
Overall Length	Lift - 105" Semi - 110" Pull - 135"
Deck Height	9 5/8"
Cutting Height	2" - 10 1/2"
Cutting Capacity	2"
Tractor H.P. Rating (PTO)	Lift-Type - 50 – 120 Pull/Semi - 30 - 120
Gearbox Rating H.P.	Center - 120 HP, Outboard 100 HP
Gearbox	540 rpm or 1000 rpm PTO Driven Gearbox Cast Iron Housing, Beveled Gears
Gearbox Lubrication	80-90W EP Gear Lube
Gearbox Input/ Output Shaft Size	Input Shaft = 1 3/4" - 20 Spline Output Shaft = 2" Dia.
Deck Material Thickness	10 gauge
Deck Side Skirt Thickness	1/4"
Skids	Replaceable
Stump Jumper	Round Pan 3/16"
Blades (4)	1/2" x 4" Heat Treated Free-Swinging Suction Blades
Blade Bolts	Keyed with Harden Flat Washer and Lock Nut
Blade Tip Speed	540 RPM 14,223 fpm 1000 RPM 14,442 fpm
Driveline	ASAE Cat 4 with Equal Angle Shaft on Pull Type
Driveline Protection	540 rpm - 4 plate slip clutch 1000 rpm - 2 plate slip clutch
Tailwheel	Semi-Mount: Lift-Type: 8' Pull-Type: 10' Pull-Type:
Wheel Bearings	2 ea. 6" x 9" x 21" Laminated 2 ea. 4" x 8" x 15 1/4" Laminated 2 ea. 6" x 9" x 21" Laminated or 24" Aircraft tires or 5" x 15" Automotive Rims 2 or 4 ea. 6" x 9" x 21" Laminated or 24" Aircraft tires or 5" x 15" Automotive Rims
Front Guard	Tapered Roller Bearing in Cast Iron Hub Optional: Chain guard or Rubber deflector
Rear Guard	Optional: Chain guard or Rubber guard
Shock Absorption	Spring Shock Absorber on Axle of Pull Type
Jack Stand	Jack Stand on Tongue of Pull Type Cutter

Designs, specifications, features and information are subject to change without notice. This web site is to be used as a guide for the matching of Land Pride Implements on Kubota Tractors in average conditions. Retail customers in conjunction with Kubota/Land pride dealers should use their best judgment to select the best combination of tractor size and implement capabilities. The mismatching of tractor and implements can result in the voiding of Kubota and/or Land Pride Warranties.